D-ORDER LEVELING CONTRACTOR OF 1929

35-081-42
VALDESE QUADRANGLE
NORTH CAROLINA
N3530-W8130/15
DIAGRAM NI 17-2
CHARLOTTE

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY


Burke, Catawba, Cleveland, Lincoln, and Rutherford Counties

Final adjustment of 1974

Edition of 10/28/75

PR: WSM/kp

NGVD 29 Elevations



NGS (USCAUR) VERTICAL CONTROL DATA (120)

Quadrangle 050314

INDEX OF PERMANENT MARKS

					•
MARK (USGS)			PAGE NO.	MARK (USGS)	PAGE NO.
1191.700			.3	17 WSM 1950 1213	11
1182 M C		Maria	3	18 WSM 1950 1295	12-
1204		NGVD 29	3	19 WSM 1950 1374	12,16
1135 ASH		Elevations	3 3 3	20 WSM 1950 1292	12
1193 ASH				21 WSM 1950 1192	13
1270 ASH			3	22 WSM 1950 1323	13
TOLUCA 1948			5,17	23 WSM 1950 1157	13,16
RLB 50 1949			5,3	24 WSM 1950 1359	14
RLB 51 1949			3	25 WSM 1950 1297	14
RLB 52 1949			4	26 WSM 1950 1481	14
RLB 58 1949			5,4.	27 WSM 1950 2574	14 / 14,15 15,16
RLB 66 1949			4	28 WSM 1950 2808	14,15
RLB 67 1949			4	29 WSM 1950 2508	15,16
RLB 68 1949			- 5	30 WSM 1950 2301	15
RLB 69 1949		-	5	31 WSM 1950 2752	15
RLB 70 1949		82	6,8,12	37 WSM 1950 2586	1.5
RLB 71 1949			. 6	38 WSM 1950 2382	15
RLB 72 1949			6,7,13		16
RLB 73 1949			7,15	40 WSM 1950 1523	. 16
RLB 74 1949			7	41 WSM 1950 1284	17
RLB 75 1949				6 ATA 1951 1249	. 17
3 WSM 1950 1			8	NOT STAMPED (1292.037)	7
4 WSM 1950 1			9	NOT STAMPED (1277.605)	8
5 WSM 1950 1			. 9	NOT STAMPED (1165.392)	8
6 WSM 1950 1			9,13	NOT STAMPED (1212.918)	. 8
7 WSM 1950 1			9		
8 WSM 1950 1			9	NGS	
9 WSM 1950 1			1.0		
10 WSM 1950			10	R V 629 (S. Ry.)	8
11 WSM 1950		,	10,10	T 60 E 1934	17
14 WSM 1950				к 131 1935	17
15 WSM 1950			11,12	V 131 RESET 1951	13,17
16 WSM 1950	1165		11	<u>,</u>	

235 Z Vert. angle elev. of 2777.8 ft @ Walker Top Church, 5way Kaylor Kus information from USGS for Kan Luttles 7/2./89

NGVD 29 Elevations	35- 081-42
, 1899-1900;	Feet
on S. side	1134.353
stamped	1192.340
nall house; und, 1951)	1269.380
rock E. found,	1202.960
ouse;	1180.605
rn Railway of center- of 6 adjacent of 6 adjacent of 6 adjacent ire company; stically in ouilding;	1191.868
nd 200 ft 4 ft W. g 6 in.;	1124.854
ine of hwy.; te hwy.	11.28.44
mi SE. along of centerline f yard; in concr 1 1949 968"	ete 968.445
TYLE AT VA I	

157 NORTH CAROLINA

VALDESE QUADRANGLE

ISOIATED BENCH MARKS (By W. S. D. Moore and C. A. Clunet Books A6201; 7630) Hodge, 300 ft E. of former post office; in large boulder of rd.; standard tablet stamped "1135 ASH" (Reported d 1949) Casar, 3.5 mi NE. of; 300 ft S. of stream; in foundation of Olive Grove Church; at SW. corner; standard tablet "1193 ASH" (Reported destroyed, 1951) Jacob Fork, 1.25 mi N. of; on E. side of rd. opposite sm in rock ledge; copper bolt stamped "1270 ASH" (Not fou Morganton, 5.4 mi S. of; opposite walnut tree; in large of rd. at stream; standard tablet stamped "1204" (Not 1951) Morganton, in NW. corner of N. portico of county courtho standard tablet stamped "1182 M C" Connelly Springs, about 0.15 mi SE. along Secondary Road post office; 148 ft N. of rail of main track of Souther Company railroad; 540 ft east of milepost 68; 29 ft N. line of road; 107 ft W. of SE. corner of most easterly buildings; 72.5 ft E. of SW. corner of most westerly of buildings; 43.5 ft W. of entrance to office of furnitude about 0.5 ft above level of concrete sidewalk; set ver S. face of S. brick wall of Hudson Furniture Company by standard tablet stamped "1191.700" (Tied by NGS, 1967) LINE 1. By R. L. Beitle, 1949; Book AV 90

Casar, 0.4 mi S. of, along State Highway 10; 50 ft N. an E. of crossroads; 57 ft SW. of SW. corner of house; 94 of centerline of street N. in concrete post projecting standard tablet stamped 'RLB 50 1949 1125"

Reference mark; 66 ft E. of tablet; 50 ft N. of centerli 28 ft W. of centerline of street N.; on top of concret right-of-way post; chiseled circle

Casar, 0.5 mi N. of, along State Highway 10, thence 1.5 dirt rd.; 3.4 mi NW. of Pleasant Hill Church; 25 ft S. of rd.; 25 ft NE. of NE. corner of house at E. edge of post projecting 6 in.; standard tablet stamped "RLB 51

Reference mark; 75 ft W. of tablet; 56 ft S. of centerline of rd.; in NE. root of 14-in. lone walnut tree; copper nail and washer

965.85

986**.7**8

U.E., Casar, 0.1 mi N. of, along State Highway 10, thence 2.5 mi SE. along dirt rd.; on NW. backwall of bridge over stream; chiseled "L"

valdese quadrangle	157 NORTH CAROLINA	35- 081	L-42
LINE 1 (Cont'd)	• •	Feet	4 <u>5</u>
1.4 mi NW. of Pleasant T-rd. E.; 28 ft S. of c standard tablet stamped Reference mark; 119 ft W	ng State Highway 10, thence 3.5 Hill Church; 33 ft S. and 80 ft eenterline of rd. E.; in concret "RLB 52 1949 1096" . of tablet; 60 ft N. and 22 ft in concrete post; iron rod	E. of e post; 1096.4	
By R. L. Beitle, 1949; B	LINE 2.	NGVD 29 Elevations	
Church; 14.8 ft S. of side of church; 48 ft	along State Highway 18, at St. 1 SE. corner and on prolongation of W. of centerline of driveway to dard tablet stamped "RLB 58 194	of E. church;	849
Reference mark; 42 ft N. step at entrance to ch	of tablet; on N. end of 1st courch; chiseled "U"	* 1082.	21
	0.8 mi SW. of; in SE. angle oppof large stone; chiseled "U"	posite 1041.	50
	LINE 3.		
By R. L. Beitle, 1949; B	ook AV 90		
	ol, 1.6 mi SE. of; on SW. side of the W. of drain crossing; on the desired of the constant of		39
18 ft E. and 24 ft N. c corner of bridge over s	8 mi E. of; 3.3 mi W. of Moriah of jct. of T-rd. N.; 21 ft SE. of tream; in concrete post project d'RLB 66 1949 1012" (Not found,	of SE. ling 6 in.;	322
Reference mark; 21 ft: NW. over stream; chiseled	of tablet; on SE. backwall of	bridge 1013.8	85
	ol, 2.6 mi E. of; 25 ft N. of T- large boulder; chiseled "U"	rd NE.; 998,	72
U.E., Golden Valley School	ol, 3.4 mi E. of; on SE. wingwal	.1 of	

bridge over stream; chiseled "L"

Golden Valley School, 1.3 mi W. of; 3.8 mi E. of, Moriah School;
21 ft S. of T-rd. N. and on prolongation of its centerline;
11 ft NW. of NW. corner of log house; in concrete post;
standard tablet stamped "RLB 67 1949 1067" (Reported destroyed,
1956)

Reference mark; 77 ft NW. of tablet; 33 ft N. of centerline of
E.-W. rd.; 36 ft W. of centerline of rd. N.; in E. base of
12-in. pine tree; rail spike

958.44

1067.109

1059.CL

U.E., Ramsey, 0.5 mi SE. of, along State Highway 18; on SW. side

Ramsey, 39 ft N. and 55 ft W. of crossroads; 29 ft E. of centerline of T-rd. N.; in concrete post; standard tablet stamped

Reference mark; 19 ft W. of tablet; 34 ft N. of centerline of State Highway 18; 12 ft E. of centerline of rd. N.; in S.

root of 14-in. twin-trunked oak tree; rail spike

1206.38

1297.286

1297.81

of rd. on SE. end of concrete headwall; chiseled "L"

"RLB 72 1949 1297"

ί

VALDESE QUADRANGLE	157 NORTH CAROLINA		35-081-42
		NGVD 29	. 8
LINE 5 (Cont'd)		Elevations	Feet
Ramsey, 4.2 mi NW. of, along State Hig along dirt rd.; 6.7 mi N. along Stat Laurel Hill; at Reynolds Grocery Sto 58 ft N. of NW. corner of store; 29 #357; in concrete post; standard tab	e Highway 18 and 450 re; 93 ft W. of hwy. ft N. of telephone p	from jct.;	1277.605
Reference mark No. 1; in root of large copper nail and washer	oak tree on W. side	of rd.;	1283.52
U.E., Laurel Hill, 5.1 mi N. of, along on W. side of hwy.; at jct. of Y-rd. concrete culvert headwall; chiscled	E.; on N. end of L-		1201.52
Laurel Hill, 4.7 mi N. of, along State N. of Catawba County line mark; 64 f Highway 450; in concrete post; standa	t E. of centerline o	f State	1165.392
U.E., Laurel Hill, 4.1 mi N. of, along on NW. wingwall of concrete bridge or			1037.98
Laurel Hill, 3.2 mi N. of, along State S. and 95 ft W. of Y-rd. fork SW.; in 5-in.; standard tablet not stamped			1212.918
"RLB 70 1949 1329" (Described in line	+)		1329.112
LIN	<u> </u>	•	
By W. S. Monk, 1950; Book AV 138			
"R V 629" (S. Ry.) (NGS)	· .		1062.567
U.E., Morganton, 2.2 mi SW. of, along thence 0.6 mi S. along dirt rd.; at a over small stream; on concrete abutme	NE. end of concrete		1028.02
LIN	3 7.	·	
By W. S. Monk, 1950; Book AV 138			
Glen Alpine, 4.6 mi SE. of; 1.1 mi SE. of Mull School; 76 ft W. of jct. of the line of rd. leading N; 7 ft NE. of comments are the comments of	Z-rd. forks; 16 ft St enterline of drive to	W. of center- o house; in	
small grassy triangle; in concrete po "3 WSM 1950 1242"	or, standard tablet	อะสแกะก	1241.416

 $\mathfrak{t}'_{\cdot,\cdot}$

	•		
VALDESE QUADRANGLE	157 NORTH CAROLINA		35-081-42
LINE 7 (Cont'd)		NGVD 29 Elevations	Feet 10
Reference mark; 18 ft E. of to oak tree; copper nail and was	ablet; in root on W. side of 6 asher	-in.	1154.12
U.E., Smarts Grove Church, 2. and dim woods rd. N.); 25 f rd. N.; on rock outcrop; ch	7 mi NW. of, along dirt rd. (j t N. of rd.; in E. track of wo iseled square	ct. of rd.	1118.99
Store; 47 ft S. of centerlin	W. of; 134 ft SW. of Z. C. Pel ne of rd.; 2 ft E. of powerlin tablet stamped "RESET 1952" (Red d elevation)	e pole;	1063.495
Reference mark; N. of tablet; gas pump; chiseled square	on SW. corner of concrete base	e of	1065.63
9 ft S. of lone gum tree; 28 side of rd. from house; on h	E. of; 25 ft E. of centerline of B ft W. of power pole; on opposingh bank; in concrete post pro let stamped "10 WSM 1950 1109"	site	1108.877
Reference mark; 9 ft S. of tal gum tree; rail spike	olet; in face on E. side of 12-	-in.	1108.79
Icard; 5.9 mi SW. of Icard F	R., thence 1.3 mi NE. along rooks. Station; 31 ft SW. and 80 ft R.E.A. pole No. 3 KEA 20; in add "11 WSM 1950 1141"	ft	1141.129
	LINE 8.		
By W. S. Monk, 1950; Book AV 1	.38		
"11 WSM 1950 1141" (Described	in line 7)		1141.129
	Jogs into Hickory quadrangle	27	
along roads to George Hildeb	on, thence 1.0 mi SE., thence or an School; 150 ft S. and 40 fresidence on W. side of rd.; ir and "14 WSM 1950 1283"	t E. of	1,282.397
Reference mark; 80 ft S. of ta oak tree; copper nail and wa		o-in.	1283.82

1.4 mi N. along State Hwy. 450; 30 ft N. and 20 ft E. junction hwy. and rd. E.; on S. end of concrete headwall of culvert;

chiseled square

1210,45

12

1433.54

1391.87

. 1292.153

1281.65

1275.71

Reference mark; 420 ft E. of tablet; 20 ft N. of hwy.; on E. end of concrete headwall of culvert; chiseled square 1347.01 U.E., Pleasant Grove Church, 0.9 mi SE. of, along State Highway 18; 90 ft S. and 15 ft E. and drive NW. to residence; on S. end of concrete headwall of culvert over stream; chiseled square. 1368.64

U.E., Pleasant Grove Church, 1.1 mi SE. of, along State Highway 18; 40 ft N. and 15 ft E. of jct. of highway and rd. W.; near crest; on S. end of stone headwall of culvert; chiseled square

U.E., Pleasant Grove Church, 1.4 mi SE. of, along State Highway 18; 0.3 mi S. of jct. of rd. W. and highway; 15 ft W. of hwy.; on SW. end of stone headwall of culvert; chiseled square

Pleasant Grove Baptist Church, 2.4 mi SE. of, along State Highway 18; 1.9 mi N. of Ramsey; 20 ft N. and 35 ft E. of jct. of bwy. and rd. E.; in concrete post; standard tablet stamped "20 WSM 1950 1292"

Reference mark; 200 ft N. of tablet; 15 ft W. of rd.; on N. end of stone headwall of culvert; chiseled square

U.E., Ramsey, 1.4 mi NW. of, along State Highway 18; 240 ft S. and 15 ft W. of jet. of highway and rd. SW. to Mt. Gilead Church; on S. and of stone headwall of culvert; chiseled square

LINE 9 (Cont'd)	Feet
U.E., Ramsey, 0.9 mi NW. of, along State Highway 18; 0.2 mi N. of Jacob Fork River; 30 ft N. and 15 ft W. of jct. drive SE.; on N. end of stone headwall of culvert; chiseled square	1191.31
U.E., Ramsey, 0.7 mi NW. of, along State Highway 18; at SE. end of concrete bridge over Jacob Fork River; on concrete abutment; chiseled square	1126.89
"RLB 72 1949 1297" (Described in line 4) (Also in line 5)	1297.286
LINE 10.	
By W. S. Monk, 1950; Book AV 138 NGVD 29 Elevations	
"V 131 RESET 1951" (NGS)	1112.183
Morganton Depot, 1.4 mi SE. of, along State Highway 18; 210 ft N. of junction of rd. leading to main hospital center; 20 ft S. of 36-in. Oak tree; in concrete post; standard tablet stamped "21 WSM 1950 1192"	1191:832
Reference mark; 20 ft N. of tablet; in face on W. side of 36-in. oak tree; rail spike	1191.50
U.E., Morganton Depot, 2.0 mi SE. of, along State Highway 18; 0.1 mi W. of junction of State Highway 18 and rd SE.; 15 ft S. of hwy.; on W. end of concrete headwall of culvert; chiseled square	1096.41
"6 WSM 1950 1229" (Described in line 7)	1229.056
Morganton, 5.4 mi SE. of, along State Highway 18; 5.0 mi NW. along State Highway 18 from Pleasant Grove Church; 57 ft SW. of jct. of T-rd. leading S. to Enola; 25 ft S. of W. end of 6 ft iron pipe culvert; 22 ft W. of centerline of rd. leading S.; in concrete post; standard tablet stamped "22 WSM 1950 1323"	1323.316
Reference mark; 520 ft S. of tablet; 15 ft W. of rd.; on center	13234310
of concrete headwall of culvert; chiseled square	1311.68
Enola, 2.7 mi E. of; 2.2 mi NW. of Pleasant Grove Chruch, along State Highway 18; 131 ft SE. of NW. fork of offset crossroads; 24 ft NE. of centerline of hwy.; 34 ft N. of centerline of bridge over stream; in concrete post projecting 6 in.; standard	
tablet stamped "23 WSM 1950 1157" 88 May Be Loot	1156.626

VALDESE QUADRANGLE	157 NORTH CA	AROLINA	NGVD 29	35- 081-42
LINE 10 (Cont'd)			Elevations	Feet
Reference mark; 150 ft Ni bridge over Henry Fork			ent of small	1160.43
U.E., Enola, 1.1 mi E. or bridge over Henry Fork	•		_	1214,66
enola, 0.2 mi S. of; 31 of centerline of rd. E. NE.; in concrete post post 124 WSM 1950 1359"	; 26 ft SE. of c	enterline of w	oods rd.	1359. 413
Reference mark; 55 ft W. pole; rail spike	of tablet; in fa	ce N. side of	telephone	1355.16
Enola, 2.3 mi S. of, alor Fire Tower; 355 ft S. of rd.; 10 ft E. of barway 6 in.; standard tablet	of Y-rd. forks; 2 to pasture; in	Oft E. of cent concrete post	terline of	1297.399
Reference mark; 600 ft S. centerline of small brittee; copper nail and w	dge; in root S.			1290.00
Enola, 3.8 mi S. of, alor Fire Tower; 24 ft E. of of school bus turning of of centerline of stream stamped "26 WSM 1950 14	Ecenterline of r Irive and 4 ft W. i; in concrete po	d.; 36 ft N. or of waiting she	f centerline ed; 44 ft W.	1480.630
Reference mark; 10 ft SE. poplar tree; copper nai		oot S. side of	7-in.	1479.81
Horse Ridge Fire Tower, a about 500 ft S. of towe Forest Rd.; 17 ft W. of ft NW. of their jct.; 6 post; standard tablet s	r; 35 ft N. of co centerline of ro ft N. of telepho	enterline of Na d. to tower; an one pole; in co	itional nd 80	2574.340
Reference mark; 9 ft W. o	•	t N. side of 4-	·in. oak	2573.45
Horse Ridge Fire Tower, 2 triangle formed by T-rd leading NESW.; in con tablet stamped "28 WSM	. forks; 16 ft Si crete post proje	E. of centerlin	ne of rd.	2807.604

VALDESE QUADRANGLE	157 NORTH CAROLINA	NGVD 29 Elevations	35-081-42 15
LINE 10 (Cont'd)	· .		Feet
Reference mark; 7 ft S. o pine tree; copper nail		le of 9 ₈ in. twin	2807.09
Horse Ridge Fire Tower, 2 C.C.C. Rd.; 440 ft SE. W. of centerline of rd. from N.; in concrete pos "29 WSM 1950 2508"	of intersection of Y-rd, ; on curve and on prolon	forks; 15 ft ngation of tangent	2508.016
Reference mark; 20 ft NW. tree; copper nail and we	•	ide of 8-in. oak	2505.28
Horse Ridge Fire Tower, 2 of centerline of rd. at curve and on prolongati rd. W.; 13.5 ft NW. of projecting 7 in.; stand	head of drain; in cent on of rd. from NW.; 0.5 14-in. red oak tree; in	er of double S. mi SE. of woods concrete post	2301.150
Reference mark; 13.5 ft S red oak tree; copper na		W. side of 14-in.	2300.57
U.E., Horse Ridge Fire To mi NW. of jct. of woods rock at culvert; chisel	rd. W.; 10 ft E. of C.		2441.04
Horse Ridge Fire Tower, 2 curve; 26 ft SE. of jct of woods rd.; in concre "31 WSM 1950 2752"	. of woods rd. S.; 9 ft	E. of centerline	2752.406
Reference mark; 20 ft SW. twin oak tree; copper n		side of 10-in.	2749.51
· .	LINE 11.		·
By W. S. Monk, 1950; Book	AV 138		•
"28 WSM 1950 2808" (Descr	ibed in line 10)		2807.604
Horse Ridge Fire Tower, 2 National Forest Road; L about midway between tw projecting 6 in.; stand	3 ft W. of centerline o in 30-in. white-oak tre	f rd.; in saddle, es; in concrete post	2585.293
Reference mark; 15 ft N. tree; copper nail and w		. side of 24-in. oak	2586.08
Horse Ridge Fire Tower, 2 National Forest Road; 1 end of saddle; 9 ft E. standard tablet stamped	6 ft S. of centerline o of 14-in. pine tree; in	f rd.; at W.	2382.073
	. •		

	VALDESE QUADRANGLE 157 NORTH CAROLINA	35-081-
``	NGV _{D 29}	33 001
	LINE 11 (Cont'd) Elevations	Feet
	Reference mark; 7 ft W. of tablet; in root on N. side of 9-in. pine tree; copper nail and washer	2382.07
·	Mt. Gilead Church, 2.0 mi W. of, along National Forest Road; 15 ft S. of centerline of rd. at bench in hill and at car turn-out; 6 ft NW. of 18-in. oak tree; in concrete post; standard tablet stamped	
	"39 WSM 1950 1913"	1912.80
·	Reference mark; 6 ft SE. of tablet; in root on N. side of 8-in. oak tree; copper nail and washer	1912.30
÷.	"RLB 73 1949 1299" (Described in line 4)	1298.62
	LINE 12.	
	By W. S. Monk, 1950; Book AV 138	
	"23 WSM 1950 1157" (Described in line 10)	1156.63
(U.E., Pleasant Grove Church, 2.0 mi NW. of, along State Highway 18; at NE. end of wooden bridge over small stream on concrete abutment; chiseled square	1154.83
	U.E., Pleasant Grove Church, 1.1 mi NE. of, along State Highway 18; at small stream crossing; 15 ft W. of highway; on N. end of concrete headwall of culvert; chiseled square	1221.70
	U.E., Pleasant Grove Church, 0.4 mi N. of; 20 ft E. of rd.; on N. end of stone headwall of culvert; chiseled square	1341.5
	"19 WSM 1950 1374" (Described in line 9)	1374.08
	LINE 13.	
	By W. S. Monk, 1950; Book AV 138	
	"29 WSM 1950 2508" (Described in line 10)	2508.01
	Golden Valley School, 5.1 mi NE. of; 130 ft S. of centerline of wooden bridge over small stream; 30 ft W. of rd.; 15 ft N. and 30 ft W. of junction of woods rd. E.; in rock boulder; standard	1519.20
	Reference mark; 50 ft E. of tablet; in face on W. side of 12-in.	
,	poplar tree; rail spike	1522.59
(

VALLESE QUADRA	ANGLE	157 NORTH CAROLINA	NGVD 29 Elevations	35-081-42 17
LINE 13 (Cont	<u>d)</u>			Feet
Tower; 130 i	ft S. and 20 ft ince; 20 ft S. o. coutcrop; standa	N. of, along rds. to Ho E. of junction of C.C.C E stream crossing on ba ard tablet stamped	. rd. and drive	1283,976
		LINE 14.		
By R. H. Paine	a, 1951; Book AV	248		
4 17 0.00	"U.E., chiseled	i square" (Described in	line 4)	1247.66
		LINE 15.		. •
By R. H. Paine	e, 1951; Book AV	248	• .	
4 46 0.00	"TOLUCA 1948 19	02" (Described in line	4)	1092.388
·		LINE 16.		
By R. H. Paine	e, 1951; Book AV	248		
5 40 8.87	"14 WSM 1950 12	83" (Described in line	8)	1282.397
		LINE 17.		
By A. T. Adams	, 1951; Book AV	232		
12 2 0.00	"K 131 1935" (N	IGS)		1195.42
12 4 2.20	70, thence 1.2 junction of rd. College Baptist	, 1.0 mi W. of, along Wmi N. along Lenior rd. E.; 6 ft N. of NW. co. Church; 12 ft SE. of t; standard tablet star	; 120 ft N. of rner Rutherford telephone pole;	1248.793
12 4 2.20		42 ft SE. of tablet; herford College Baptis		1249.85
		LINE 18.		
By A. T. Adams	, 1951; Book AV	232		
9 1 0.00	"V 131 RESET 19	51 (NGS) (Also in line	.10)	1112.183
9 1 0.00	"T 60 E 1934" (NGS)		1114.755

Ú,

LINE 18 (Cont'd)

<u>Feet</u>


9 2 1.30 U.E., 70 ft N. of Lenior Street crossing State Highway 18; on SE. end of concrete base of Shell gas pumps; chiseled square

1202.23

NGVD 29 Elevations

	A CONTRACTOR OF THE PROPERTY O	
	* NAD 27 * INVERSE PROGRAM FOR	STATIONS NOT IN THE DATA BASE
1	FROM STA => 2-352 1948	TO STA =>
	LATITUDE => 35° 38° 22.63000" LONGITUDE => 81° 43° 24.40000"	LATITUDE => LONGITUDE =>
	North (Y) => 698800.587 F East (X) => 1190890.057 F	North (Y) => East (X) =>
ELEV (M) => 2777,800 F		ELEV (M) =>
	THETA 0 - 1° 34° 18.81" SCALE FACTOR 0.99989543 COMBINE FACTOR 0.99976255	THETA 0 SCALE FACTOR COMBINE FACTOR
	N FORWARD GEO AZ N BACKWARD GEO AZ	N FORWARD GRID AZ N BACKWARD GRID AZ
	GEODETIC DISTANCE GRID DISTANCE	Another Inverse ? Y or N

By HSGS ROLLA, MO. BM 2-35 7 1948 is 58.78 feel in true of a special con unre



NGVD 29 Elevations