

HIGH-ORDER LEVELING  
NATIONAL GEODETIC VERTICAL DATUM OF 1929

35-080-41  
MOCKSVILLE QUADRANGLE  
187 NORTH CAROLINA  
113545-W8030/15  
DIAGRAM NI 17-2  
CHARLOTTE

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY


Davie, Iredell, and Rowan Counties

Final adjustment of 1975

Edition of 11/20/75

PR: WSM/rmc

NGVD 29  
Elevations



(USC&GS) VERTICAL CONTROL DATA

A. Quadrangle 350804

THIRD-ORDER LEVELING  
NATIONAL GEODETIC VERTICAL DATUM OF 1929

35-080-41  
MOCKSVILLE QUADRANGLE  
187 NORTH CAROLINA  
N3545-W8030/15  
DIAGRAM NI 17-2  
CHARLOTTE


UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Davie, Iredell, and Rowan Counties

Final adjustment of 1975

Edition of 11/20/75

PR: WSM/rac



NGS (USNGS) VERTICAL CONTROL DATA

A. Quadrangle 350804

187

167 NORTH CAROLINA  
MOCKSVILLE QUADRANGLE35-080-41  
N3545-W8030/15

## INDEX OF PERMANENT MARKS

<u>MARK (USGS)</u>	<u>PAGE NO.</u>	<u>MARK (USGS)</u>	<u>PAGE NO.</u>
TT 46 HF 1948 676	3	400 JAS 1965 782	10
TT 47 HF 1948 741	3	401 JAS 1965 678	10
TT 54 HF 1948 825	4	402 JAS 1965 786	10
123 WSM 1949 755	3	403 JAS 1965 789 ET	10
124 WSM 1949 781	3	404 JAS 1965 688	9
86 DOP 1962 RESET 1966 896	4,7	405 JAS 1965 826	8,9
87 DOP 1962 862	4	406 JAS 1965 702	8
365 JAS 1965 913	5	407 JAS 1965 810	8
366 JAS 1965 918	5	408 JAS 1965 713	7,8
367 JAS 1965 895	5,7	409 JAS 1965 708	7
368 JAS 1965 748	5	410 JAS 1965 881	7
373 JAS 1965 727	4	411 JAS 1965 871	7
374 JAS 1965 849	4,9,12	412 JAS 1965 756	7
375 JAS 1965 899	4	413 JAS 1965 811	7
376 JAS 1965 803	9	414 JAS 1965 882	6,7
377 JAS 1965 861	9	415 JAS 1965 890	6
378 JAS 1965 854	9,10	416 JAS 1965 894	6
379 JAS 1965 815	9	417 JAS 1965 835	6
380 JAS 1965 711	9	418 JAS 1965 773	6
381 JAS 1965 706	8	419 JAS 1965 782	6
382 JAS 1965 812	8	420 JAS 1965 684	5
385 JAS 1965 772	12	421 JAS 1965 721	5
386 JAS 1965 755	11	422 JAS 1965 761	5
387 JAS 1965 759	11	423 JAS 1965 701	5
388 JAS 1965 762	11		
389 JAS 1965 663	11	<u>NGS</u>	
390 JAS 1965 668	11	814.293 L 42 1932	8
391 JAS 1965 758	11	CANA 1948 AZ MK	6
392 JAS 1965 700	11	CENTER NO 1 1948	8
393 JAS 1965 651	11	CENTER NO 2 1948	8
394 JAS 1965 647	10	NEEDMORE 1948	10,12

NGVD 29  
Elevations

MOCKSVILLE QUADRANGLE  
Book AV 136

187 NORTH CAROLINA

W. S. Monk

35-080-41

3

1949

LINE 1.

Feet

By W. S. Monk, 1949; Book AV 136

- Fork, 4.9 mi SW. of, along State Highway 801, thence 1.9 mi NE. along Graves Road; 6.8 mi SW. of Cornatzer, along rds. SW. to Terrentine; 25 ft N. and 40 ft W. of centerline of Graves Road at junction of rd. NE.; in concrete post; standard tablet stamped "123 WSM 1949 755" (Not found, 1967) 754.921
- Cornatzer, 4.7 mi SW. of, along rds. to Terrentine Church; in line with centerline of rd. NE. to Cornatzer; 20 ft S. of centerline of rd. SE. to Terrentine Church; in concrete post; standard tablet stamped "124 WSM 1949 781" (Disturbed, 1969) 781.439
- Reference mark; 110 ft N. of tablet; 90 ft N. and 25 ft E. of centerline of rd. at junction of rd.; in root on W. side of 12 in. oak tree; copper nail and washer 782.88
- U.E., Cornatzer, 3.5 mi SW. of, along rd. to Terrentine; 20 ft S. and 80 ft E. of centerline of Terrentine-Cornatzer rd. at junction of U. S. Highway 64; on SE. end of concrete headwall of culvert; chiseled square 732.04

LINE 2.

By W. S. Monk, 1949; Book AV 136

- Davie Crossroads, 2.8 mi S. of, along U. S. Highway 601; 42 ft S. and 13 ft W. of centerline of I-rd. W.; 26 ft W. of centerline of hwy.; in fence corner; in concrete post; standard tablet stamped "TT 47 HF 1948 741" (Not found, 1966) 741.403
- Reference mark; 100 ft SE. of tablet; on NE. corner of concrete headwall of culvert; chiseled square 736.98
- U.E., Davie Crossroads, 4.4 mi S. of, along U. S. Highway 601; on SE. concrete abutment of concrete bridge over South Yadkin River; chiseled square 650.65
- Davie Crossroads, 5.2 mi S. of, along U. S. Highway 601; 40 ft E. of centerline of hwy.; 14 ft S. of telephone pole; 15 ft W. of 6 in. pine tree; in concrete post; standard tablet stamped "TT 46 HF 1948 676" (Reported destroyed, 1966) 676.175
- Reference mark; 10 ft NE. of tablet; in root on W. side of 6 in. pine tree; copper nail and washer 675.19
- U.E., Davie Crossroads; 5.7 mi S. of, along U. S. Highway 601; on NE. abutment of concrete bridge over Second Creek; chiseled square 646.61

NGVD 29  
Elevations

1951

LINE 3.

Feet

By J. E. McClane, 1951; Book AV 242

Smith Grove Methodist Church; about 300 ft N. of; 25 ft SE. of centerline of U. S. Highway 158; 8 ft S. at fence corner; in concrete post; standard tablet stamped "TT 54 HF 1948 825"

824.868

LINE 4.

By D. O. Pruitt, 1962; Book AV 872

6 28 5.41 Lone Hickory, 4.8 mi S. of, along County Road 2105, thence 3.2 mi E. along County Roads 2179 and 1320; 21 ft N. and 20 ft W. of, and 1.0 ft lower than centerline of rd. at junction of drive to Bear Creek Baptist Church; 93 ft S. of SE. corner of church; in concrete block level with ground; standard tablet stamped "86 DOP 1962 RESEY 1966 896"

895.420

6 31 7.41 Lone Hickory, 4.3 mi S. of, along County Road 2105, thence 4.2 mi E. along County Roads 2179 and 1320, thence 0.4 mi N. along County Road 1002, thence 0.6 mi NW. along County Road 1332; 2.5 mi W. of Farmington, along State Highway 801, thence 0.7 mi S. along County Road 1411, thence 1.5 mi W. along County Road 1420, thence 0.3 mi S. along County Road 1419, thence 0.8 mi W. along County Road 1415, thence 0.6 mi SW. along Road 1332; 53 ft E. of centerline of crossroads (County Roads 1333 and 1332); in top of Sinclair gasoline pump platform; standard tablet stamped "87 DOP 1962 862"

861.626

GAS ISLAND REMOVED

LINE 5.

DEST. 3/17/98 *WB*

By R. L. Meador, 1966; Book AV 1434

2 31 8.48 Cook Spring, 1.2 mi SW. of Cool Spring School, along U. S. Highway 64; about 75 ft S. of, and 3.0 ft lower than centerline of Highway 64 at junction of County Road 2301 SE.; 0.4 ft N. of metal witness post; in concrete post projecting 4 in. above ground; standard tablet stamped "375 JAS 1965 899"

898.728

2 33 10.10 Cool Spring, 0.4 mi NE. of Cool Spring School, along U. S. Highway 64, thence 0.05 mi SE. along County Road 1003; 27 ft NE. of, and about 1.0 ft higher than centerline of rd.; 0.5 ft SW. of metal witness post; in concrete post projecting 3 in. above ground; standard tablet stamped "374 JAS 1965 849"

848.682

2 35 10.92 Cool Spring, 0.2 mi NE. of Cool Spring School, along U. S. Highway 64, thence 0.8 mi NW. along County Road 2163; level with center of bridge over Five Mile Branch; in top of NW. end of SW. abutment of bridge; standard tablet stamped "373 JAS 1965 721"

726.701

[Jogs into Statesville quadrangle]

NGVD 29  
Elevations

LINE 5 (Cont'd)Feet

- 2 46 16.74 Harmony, 0.1 mi S. of post office, along U. S. Highway 21, thence 4.9 mi SE. along State Highway 901, thence 1.4 mi SW. along County Road 2158; about 30 ft SE. of, and 5.0 ft lower than centerline of rd.; in top of NE. end of SE. concrete headwall of bridge over small stream; standard tablet stamped "368 JAS 1965 748" 747.752
- 2 48 18.19 Harmony, 0.1 mi S. of post office, along U. S. Highway 21, thence 5.0 mi SE. along State Highway 901; about 0.1 mi SE. of junction of Highway 901 and County Road 2158 SW.; about 30 ft NE. of, and 1.0 ft lower than centerline of rd.; 0.6 ft SW. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "367 JAS 1965 895" 895.126
- 2 49 19.49 Harmony, 0.1 mi S. of post office, along U. S. Highway 21, thence 3.7 mi SE. along State Highway 901; about 50 ft W. of, and 1.0 ft lower than centerline of Highway 901 at junction of County Road 2128 E.; 0.5 ft E. of metal witness post projecting 1 in. above ground; standard tablet stamped "366 JAS 1965 918" 917.351
- 2 50 20.70 Harmony, 0.1 mi S. of post office, along U. S. Highway 21, thence 2.4 mi SE. along State Highway 901; about 50 ft SW. of, and 2.0 ft lower than centerline of Highway 901 at junction of County Road 2132 S.; about 9 ft SW. of power pole No. 46; 0.5 ft E. of metal witness post; in concrete post projecting 2 in. above ground; standard tablet stamped "365 JAS 1965 913" 912.772

LINE 6.

By R. L. Meador, 1966; Book AV 1434

- 3 2 0.94 Farmington, 0.6 mi S. of Farmington School, along County Road 1410; about 100 ft S. of center of bridge over Cedar Creek; 30 ft E. of, and about 10.0 ft lower than centerline of rd.; 0.5 ft W. of metal witness post; in concrete post projecting 2 in. above ground; standard tablet stamped "423 JAS 1965 701" 700.724
- 3 4 1.99 Farmington, 1.7 mi S. of Farmington School, along County Road 1410; about 40 ft NE. of and 3.0 ft lower than centerline of Road 1410 at junction of County Road 1437 E.; 0.4 ft SW. of metal witness post; in concrete post projecting 2 in. above ground; standard tablet stamped "422 JAS 1965 761" 760.783
- 3 5 3.41 Farmington, 3.2 mi S. of Farmington School, along County Road 1410; opposite telephone pole No. 28; about 21 ft W. of, and 1.0 ft higher than centerline of rd.; 0.5 ft E. of metal witness post; in concrete post projecting 3 in. above ground; standard tablet stamped "421 JAS 1965 721" 721.229
- 3 7 4.70 Mocksville, 4.4 mi N. of courthouse, along U. S. Highway 158; 4.3 mi S. of Farmington School at Farmington, along County Road 1410, thence 0.3 mi S. along Highway 158; in top of SE. end of NE. abutment of bridge over Dutchmans Creek; standard tablet stamped "420 JAS 1965 684" 683.760

Good 1990/oct

NGVD 29  
Elevations

LINE 6 (Cont'd)feet

- |      |       |  |         |
|------|-------|--|---------|
| 3 8  | 5.54  | Mocksville, 3.9 mi N. of courthouse, along U. S. Highway 158, thence 0.3 mi W. along County Road 1409, thence 0.2 mi SW. along County Road 1406; about 400 ft SSW. of junction of Road 1406 and County Road 1407 NW.; about 27 ft SE. of, and 3.0 ft lower than centerline of rd.; 0.5 ft NW. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "419 JAS 1965 782"  | 781.796 |
| 3 11 | 6.82  | Mocksville, 3.9 mi N. of courthouse, along U. S. Highway 158, thence 0.3 mi W. along County Road 1409, thence 0.1 mi SW. along County Road 1406, thence 1.2 mi NW. along County Road 1407; about 36 ft N. of, and 3.0 ft higher than centerline of rd. at junction of woods rd. NE.; about 7 ft W. of telephone pole No. 69; 0.5 ft S. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "418 JAS 1965 773" | 772.575 |
| 3 14 | 8.55  | Mocksville, 4.6 mi NW. of post office, along U. S. Highway 601, thence 0.8 mi E. along County Road 1408; about 45 ft S. of, and 3.0 ft lower than centerline of Road 1408 at junction of County Road 1407 E.; about 15 ft SW. of power pole; 0.4 ft NW. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "417 JAS 1965 835"  | 834.627 |
| 3 15 | 9.29  | Mocksville, 4.6 mi NW. of post office, along U. S. Highway 601; about 225 ft E. of junction of Highway 601 and County Road 1408 E.; about 21 ft S. of, and 1.0 ft lower than centerline of rd.; 2 ft N. of wire fence; 0.5 ft N. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "414 JAS 1965 882"   | 881.507 |
| 3 16 | 10.52 | Mocksville, 5.9 mi NW. of post office, along U. S. Highway 601; about 225 ft SE. of junction of Highway 601 and County Road 1412 NE.; about 30 ft E. of, and level with centerline of rd.; about 100 ft N. of telephone pole No. 33; about 80 ft S. of telephone pole No. 34; 0.5 ft W. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "415 JAS 1965 890"  | 889.463 |
| 3 17 | 11.76 | Mocksville, 1.0 mi NW. of junction of U. S. Highways 158 and 601-64, along Highway 601-64 to junction of U. S. Highway 601 and 64, thence 6.2 mi NW. (right) along Highway 601; 16 ft E. of, and 1.0 ft higher than centerline of rd. at junction of drive E.; in concrete post projecting 3 in.; NGS standard azimuth mark disk stamped "CARA 1948"   | 903.596 |
| 3 18 | 12.96 | Mocksville, 7.3 mi NW. of post office, along U. S. Highway 601, thence 1.2 mi NW. along County Road 1002; about 75 ft S. of, and 3.0 ft lower than centerline of Road 1002 at junction of 1320 W.; 0.5 ft NE. of metal witness post; in concrete post level with ground; standard tablet stamped "416 JAS 1965 894"  | 893.449 |

NGVD 29  
Elevations

LINE 6 (Cont'd)Feet

3 19 13.94 "86 DOP 1962 RESET 1966 896" (Described in line 4) 895.420

LINE 7.

By R. L. Meador, 1966; Book AV 1434

3 21 0.00 "414 JAS 1965 882" (Described in line 6) 881.507

3 22 1.04 Mocksville, 4.4 mi NW. of post office, along U. S. Highway 601, thence 0.8 mi W. along County Road 1307; 1.6 mi E. of I. James Crossroads Baptist Church; about 90 ft W. of, and 1.0 ft lower than centerline of rd. at junction of woods rd. N.; 0.4 ft S. of metal witness post; in concrete post level with ground; standard tablet stamped "413 JAS 1965 811" (Reported destroyed, 1969) 810.617

3 24 1.92 Mocksville, 4.4 mi NW. of post office, along U. S. Highway 601; 0.7 mi E. of I. James Crossroads Baptist Church; in top of NW. end of SW. abutment of bridge over Bear Creek; standard tablet stamped "412 JAS 1965 756" (Reported destroyed, 1969) 756.211

3 26 2.67 Mocksville, 5.2 mi W. of post office, along U. S. Highway 64, thence 1.0 mi NW. along County Road 1306; at I. James Crossroads Baptist Church; about 63 ft S. of, and 2.0 ft lower than centerline of Road 1306 at junction of County Road 1307 W.; 0.5 ft NE. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "411 JAS 1965 871" 870.835

3 28 4.20 Mocksville, 6.6 mi W. of post office, along U. S. Highway 64; about 150 ft W. of junction of Highway 64 and County Road 1307 N.; about 25 ft N. of, and 5.0 ft lower than centerline of rd. at small stream crossing; in top of E. end of N. headwall of large concrete culvert; standard tablet stamped "408 JAS 1965 713" 712.878

3 30 5.00 Mocksville, 7.5 mi W. of post office, along U. S. Highway 64; 0.5 ft higher than center of bridge over Hunting Creek; in top of E. end of S. wheelguard of bridge; standard tablet stamped "409 JAS 1965 708" 708.029

3 32 6.52 Mocksville, 9.0 mi W. of post office, along U. S. Highway 64; about 0.2 mi SW. of junction of Highway 64 and State Highway 901 W.; about 25 ft NW. of, and 2.0 ft higher than centerline of Highway 64; 9 ft SW. of fence corner; 0.5 ft SE. of metal witness post; in concrete post projecting 2 in. above ground; standard tablet stamped "410 JAS 1965 881" 880.615

3 33 8.12 "367 JAS 1965 893" (Described in line 5) 895.126



1966

LINE 8.

By R. L. Meador, 1966; Book AV 1434

3 35	0.00	"814.293 L 42 1932" (NGS)	814.263
3 37	1.75	Mocksville, 0.1 mi S. of post office, along U. S. Highway 64; thence 1.3 mi W. along County Road 1140; 1.2 mi W. of Mocksville Fire Station; 61 ft SE. of, and about 7.0 ft lower than center of bridge over Bear Creek; 35 ft S. of, and about 7.0 ft lower than centerline of rd.; 2 ft N. of wire fence; 0.4 ft N. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "406 JAS 1965 702"	702.234
3 39	3.19	Mocksville, 0.1 mi S. of post office, along U. S. Highway 64, thence 2.8 mi W. along County Road 1140; 2.7 mi W. of Mocksville Fire Station; about 22 ft SW. of, and level with centerline of Road 1140 at junction of County Road 1116; 0.4 ft NW. of metal witness post; in concrete post projecting 3 in. above ground; standard tablet stamped "405 JAS 1965 826"	826.144
3 41	4.79	Mocksville, 3.3 mi W. of post office, along U. S. Highway 64; about 40 ft N. of, and 1.0 ft lower than centerline of Highway 64 at junction of County Road 1116 S.; 0.4 ft SW. of metal witness post; in concrete post level with ground; standard tablet stamped "407 JAS 1965 810"	810.409
3 43	6.56	Mocksville, about 5.0 mi NW. of, along N. side of U. S. Highway 64; 33 ft S. of centerline of hwy.; 1 ft N. of fence line; in concrete post projecting 5 in.; NGS standard reference mark disk stamped "CENTER NO 1 1948" (Not found, 1967)	849.647
3 43	6.56	Mocksville, about 5.0 mi NW. of; 38 ft N. of centerline of hwy.; 30 ft W. of centerline of paved rd.; 2 ft N. of power pole; in concrete post projecting 5 in.; NGS standard reference mark disk stamped "CENTER NO 2 1948"	856.472
3 45	7.93	"408 JAS 1965 713" (Described in line 7)	712.878

LINE 9.

By R. L. Meador, 1966; Book AV 1434

3 53	4.59	Cleveland, 2.3 mi N. of post office, along County Road 1957; about 48 ft NW. of, and level with centerline of Road 1957 at junction of County Road 1972; about 6 ft E. of power pole; 0.5 ft SE. of metal witness post; in concrete post projecting 2 in. above ground; standard tablet stamped "382 JAS 1965 812"	812.180
3 55	5.61	Cleveland, 3.3 mi N. of post office, along County Road 1957; 75 ft NE. of, and about 4.0 ft lower than center of bridge over Fourth Creek; 32 ft E. of, and about 4.0 ft lower than centerline of rd.; 0.4 ft NW. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "381 JAS 1965 706"	706.409

LINE 9 (Cont d)Feet

3	57	6.44	Cleveland, 4.2 mi N. of post office, along County Road 1957; 58 ft NE. of and about 2.0 ft lower than center of bridge over small stream; 22 ft E. of, and 1.0 ft lower than centerline of rd.; 0.5 ft W. of metal witness post; in concrete post level with ground; standard tablet stamped "380 JAS 1965 711"	710.491
3	59	7.48	Cool Spring, 0.4 mi NE. of Cool Spring School, along U. S. Highway 64, thence 5.0 mi SE. along County Road 1003; 5.3 mi N. of post office at Cleveland, along County Road 1957; about 200 ft NW. of junction of Roads 1003 and 1957 SW.; 25 ft NE. of, and 2.0 ft lower than centerline of rd.; 0.4 ft SW. of metal witness post; in concrete post projecting 3 in. above ground; standard tablet stamped "379 JAS 1965 815"	815.411
3	60	8.63	Cool Spring, 0.4 mi NE. of Cool Spring School, along U. S. Highway 64, thence 3.7 mi SE. along County Road 1003; about 0.1 mi NW. of junction of Road 1003; about 0.1 mi NW. of junction of Road 1003 and County Road 1984 NE.; about 30 ft SW. of and 4.0 ft higher than centerline of rd.; about 18 ft SSE. of telephone pole No. 170; 0.5 ft NE. of metal witness post; in concrete post projecting 2 in. above ground; standard tablet stamped "378 JAS 1965 854"	853.745
3	62	9.81	Cool Spring, 0.4 mi NE. of Cool Spring School, along U. S. Highway 64, thence 2.5 mi SE. along County Road 1003; opposite country church; about 40 ft SW. of, and 1.0 ft higher than centerline of Road 1003 at junction of County Road 1979; 9 ft SW. of telephone pole No. 200; 0.5 ft N. of metal witness post; in concrete post projection 1 in. above ground; standard tablet stamped "377 JAS 1965 861"	861.129
3	63	11.05	Cool Spring, 0.4 mi NE. of Cool Spring School, along U. S. Highway 64, thence 1.2 mi SE. along County Road 1003; about 45 ft NE. of, and 2.0 ft higher than centerline of rd. at Iredell-Rowan County line; 0.6 ft S. of metal witness post; in concrete post projecting 6 in. above ground; standard tablet stamped "376 JAS 1965 802"	803.050
3	65	12.20	"374 JAS 1965 845" (Described in line 5)	848.682

LINE 10.

By R. L. Meador, 1966; Book AV 1434

4	1	0.00	"405 JAS 1965 826" (Described in line 9)	826.144
4	2	1.69	Cool Spring, 3.1 mi NE. of Cool Spring School, along U. S. Highway 64, thence 3.0 mi SE. along County Road 1159, thence 2.7 mi E. along County Road 1147; about 1.0 ft higher than center of bridge over Hunting Creek; in top of SE. end of SW. wheelguard of bridge; standard tablet stamped "404 JAS 1965 688"	688.320

LINE 10 (Cont'd)Feet

4	4	2.87	Cool Spring, 3.1 mi NE. of Cool Spring School, along U. S. Highway 64, thence 3.0 mi SE. along County Road 1159, thence 1.5 mi E. along County Road 1147; about 80 ft SE. of, and 3.0 ft higher than centerline of Road 1147 at junction of County Road 1143; 0.5 ft SW. of metal witness post; in concrete post projecting 3 in. above ground; standard tablet stamped "403 JAS 1965 789 ET"	789.314
4	6	4.35	Cool Spring, 3.1 mi NE. of Cool Spring School, along U. S. Highway 64, thence 3.0 mi SE. along County Road 1159; about 175 ft NW. of centerline of Road 1159 at junction of County Road 1147 SE.; about 33 ft SW. of, and 1.0 ft lower than centerline of rd.; 0.4 ft NE. of metal witness post; in concrete post projecting 3 in. above ground; standard tablet stamped "402 JAS 1965 786"	786.011
4	8	5.48	Cool Spring, 3.1 mi NE. of Cool Spring School, along U. S. Highway 64, thence 4.2 mi SE. along County Road 1159; about 75 ft S. of, and 4.0 ft lower than center of bridge over South Yadkin River; about 20 ft W. of, and 4.0 ft lower than centerline of rd.; about 12 ft SW. of SW. corner of bridge; 0.4 ft E. of metal witness post; in concrete post level with ground; standard tablet stamped "401 JAS 1965 678"	677.782
4	10	6.50	Cool Spring, 3.1 mi NE. of Cool Spring School, along U. S. Highway 64, thence 4.2 mi SE. along County Road 1159, thence 1.1 mi S. along County Road 1972; about 150 ft N. of junction of Road 1972 and County Road 1981; about 24 ft W. of, and 1.0 ft lower than centerline of rd.; 6 ft NE. of power pole; 0.5 ft E. of metal witness post; in concrete post projecting 4 in. above ground; standard tablet stamped "400 JAS 1965 782"	782.497
4	12	7.55	Cleveland, 6.0 mi N. of; 1.2 mi NW. of Needmore; on property owned by Jerusalem Holiness Church; 111 ft SE. of SW. corner of church; 56 ft NW. of centerline of crossroads; 47 ft N. of centerline of dirt rd.; 32 ft W. of centerline of dirt rd.; in concrete post projecting 3 in.; NGS standard triangulation disk stamped "NEEDMORE 1948"	825.287
4	14	9.52	"378 JAS 1965 854" (Described in line 9)	853.745

LINE 11.

By R. L. Meador, 1966; Book AV 1434

4	35	9.05	Coolcreek, 0.5 mi SW. of post office, along State Highway 801, thence 3.1 mi E. along County Road 1103, thence 3.3 mi S. along U. S. Highway 601; level with center of bridge over Second Creek; in top of E. end of N. abutment of bridge; standard tablet stamped "394 JAS 1965 647"	646.598
---	----	------	--	---------

NGVD 29  
Elevations

LINE 11 (Cont'd)

		<u>Feet</u>
4 26	10.41 Cooleegee, 0.5 mi SW. of post office, along State Highway 801, thence 3.1 mi E. along County Road 1103, thence 1.9 mi S. along U. S. Highway 601; level with center of bridge over South Yackin River; in top of NE. end of NW. abutment of bridge; standard tablet stamped "393 JAS 1965 651"	650.647
4 38	11.62 Cooleegee, 0.5 mi SW. of post office, along State Highway 801, thence 3.1 mi E. along County Road 1103, thence 0.6 mi S. along U. S. Highway 601; about 45 ft NW. of, and 2.0 ft lower than centerline of Highway 601 at junction of County Road 1819 E.; in top of N. end of W. headwall of concrete culvert; standard tablet stamped "392 JAS 1965 700"	699.547
4 40	13.16 Cooleegee, 0.5 mi SW. of post office, along State Highway 801, thence 2.1 mi E. along County Road 1103; about 45 ft SW. of, and 6.0 ft higher than centerline of Road 1103 at junction of County Road 1101 S.; 0.5 ft N. of metal witness post; in concrete post level with ground; standard tablet stamped "391 JAS 1965 758"	758.317
4 42	14.40 Cooleegee, 0.5 mi SW. of post office, along State Highway 801, thence 0.8 mi E. along County Road 1103; level with center of bridge over small stream; in top of SW. end of NW. abutment of bridge; standard tablet stamped "390 JAS 1965 668"	667.630
4 44	15.37 Cooleegee, 0.8 mi SW. of post office, along State Highway 801; about 1.0 ft higher than center of bridge over South Yackin River; in top of NE. end of NW. wheelguard of bridge; standard tablet stamped "389 JAS 1965 663"	662.533
4 46	16.47 Cooleegee, 1.3 mi SW. of post office, along State Highway 801, thence 0.6 mi W. along County Road 1984; about 30 ft NE. of, and 2.0 ft lower than centerline of rd.; 5 ft NW. of telephone pole No. 24; 0.4 ft SW. of metal witness post; in concrete post level with ground; standard tablet stamped "388 JAS 1965 762"	761.798
4 47	17.68 Cooleegee, 1.3 mi SW. of post office, along State Highway 801, thence 1.9 mi W. along County Road 1984; about 80 ft SE. of, and level with centerline of bridge over RR. (RR. is 24.0 ft lower than center of bridge); about 25 ft S. of, and 1.0 ft lower than centerline of rd.; 31 ft E. of telephone pole No. 61; 0.4 ft N. of metal witness post; in concrete post projecting 1 in. above ground; standard tablet stamped "387 JAS 1965 759"	758.490
4 48	18.64 Cooleegee, 1.3 mi SW. of post office, along State Highway 801, thence 2.9 mi W. along County Road 1984; about 75 ft NE. of, and 3.0 ft lower than centerline of Road 1894 at junction of County Road 1981 N.; 0.5 ft S. of metal witness post; in concrete post projecting 2 in. above ground; standard tablet stamped "386 JAS 1965 755"	755.027