

WAYAH BALD
QUAD.

STATE N.C.

R.P. Willingham, 1936

By

91
ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)THIRD
ORDER
PK. 26908

ADJ. 1929 General

Recopy
10/11/49 CMRNORTH CAROLIN.
WAYAH BALD QUADRANGLE
(Latitude 35°-35°15'; Longitude 83°30'-83°45')
MACON, CLAY, CHEROKEE AND GRAHAM COUNTIES

Third-order leveling:

FROM CULLASAJA QUADRANGLE WEST ALONG ROADS BY WAY OF
ACUONE INTO BIG STAMP KNOB QUADRANGLE (by R.P. Willingham
in 1936)Elevations
NGVD 29Frankline, 5.3 mi. SW. thence 2.7 mi. W. from, 50 ft.
NW. of entrance to State Game Refuge, 30 ft. W.
of center line of rd., in root on SW. side of
10-in. oak tree; copper nail and washer, painted
"U.S. 2247.3 B.M."

2,248.69

Frankline, 5.3 mi. SW. thence 2.9 mi. W. from, on
Andrews Road, 1,100 ft. W. of W. entrance to State
Game Refuge, 125 ft. W. and 25 ft. N. of T-rd. S. at
rock quarry, 25 ft. N. of center line of rd., in top
of sandstone outcrop; standard tablet stamped
"K 3 1933," painted "U.S.P.D.M. 2268.5"

2,269.873 -

Reference mark, 35 ft. E. of tablet, on N. side of
rd., in root on S. side of 14-in. oak tree; copper nail
and washer

2,272.76

Frankline, 5.3 mi. SW. thence 3.2 mi. W. from, on
Andrews Road, 35 ft. W. of T-rd. E. to Wayah Equipment
Depot, 30 ft. W. of Game Refuge sign, in root on SW.
side of 24-in. oak tree; copper nail and washer, painted
"U.S. 2284.5 B.M."

2,285.88

Frankline, 5.3 mi. SW. thence 3.7 mi. W. from, on
Andrews Road, 30 ft. N. of center line of rd.,
4 ft. W. of N-S fence line, 15 ft. N. of E-W
fence line, in root on S. side of 14-in. walnut tree;
copper nail and washer, painted "U.S. 2325.8 B.M."

2,325.17

Franklin, 5.3 mi. SW. thence 4 mi. W. from, on Andrews
Road, in front of residence of Babbling Brook Farm,
at sign Franklin 9 miles, Acuone 13 miles, in root
on SW. side of 30-in. white pine tree; copper nail
and washer, painted "U.S. 2346.7 B.M."

2,348.04

Franklin, 5.3 mi. SW. thence 4.5 mi. W. from, on
Andrews Road, about 130 ft. W. of right angle turn,
on N. side of rd., in root on S. side of 30-in. oak tree;
copper nail and washer, painted "U.S. 2420.9 B.M."

2,422.36

QUAD. WAYAH BALD STATE N.C. By ALTITUDE ABOVE
 ORDER THIRD ADJ. 1929 General MEAN SEA LEVEL
 BK. D6908 (Feet)
 Recopy
 10/11/49 CMR -2- NGVD 29
 Elevations

Franklin, 5.3 mi. SW. thence 4.9 mi. W. from, on
 Andrews Road, 20 ft. S. of center line of rd.,
 between rd. and creek, in root on N. side of 14-in.
 oak tree; copper nail and washer, painted "U.S.
 2485.9 B.M." 2,487.23

Franklin, 5.3 mi. SW. thence 5.5 mi. W. from, 70 ft.
 NW. of intersection of dim logging rd., 40 ft.
 N. of rd., in root on SW. side of 14-in. birch tree;
 copper nail and washer, painted "U.S. 2583.0 B.M." 2,584.31

Franklin, 5.3 mi. SW. thence 6.1 mi. W. from, on
 Andrews Road, 50 ft. S. of center line of rd., in top
 of sandstone boulder; standard tablet stamped
 "K 5 1933", painted "U.S. 2800.1 P.B.M." 2,801.593

Reference mark, 130 ft. NW. of tablet, 40 ft. N. of
 rd., in root on S. side of 20-in. white oak tree;
 copper nail and washer 2,808.44

Franklin, 5.3 mi. SW. thence 6.6 mi. W. from, on
 Andrews Road, 30 ft. S. of center line of rd., 7 ft.
 N. of stream, in root on N. side of 12-in. hemlock tree;
 copper nail and washer, painted "U.S. 3052.8 B.M." 3,054.34

Franklin, 5.3 mi. SW. thence 7.2 mi. W. from, on
 Andrews Road, 35 ft. S. of center line of rd., at
 drain crossing, at E. edge of stream, in root on N.
 side of 16-in. poplar tree; copper nail and washer,
 painted "U.S. 3295.6 B.M." 3,297.16

Wayah Gap, 0.9 mi. E. of, 25 ft. S. of center line
 of rd., at drain crossing, at W. edge of stream,
 on top of sandstone boulder; chiseled square 3,817.62

Wayah Gap, 150 ft. S. of rd. intersection, 70 ft.
 E. of rd. leading S., 150 ft. S. of Andrews Road,
 15 ft. N. of 24-in. oak tree, in concrete post;
 standard tablet stamped "K 6 1933," painted U.S.
 4178.0 P.B.M." 4,180.013

Reference mark, 60 ft. W. and 15 ft. N. of tablet,
 in root on E. side of 30-in. oak tree; copper nail and
 washer 4,168.69

Wayah Gap, 0.8 mi. W. of, 6.4 mi. E. of Aquone, 55 ft.
 N. of center line of rd., in root on S. side of 20-in.
 oak tree; copper nail and washer, painted "U.S. 3934.0
 B.M." 3,936.04

QUAD. WAYAN BALD STATE N.C. BY ...
 ORDER THIRD ADJ. 1929 General
 BK.B6908
 Recopy
 10/11/49 CNR -3-
 ALTITUDE ABOVE
 MEAN SEA LEVEL
 (Feet)
 NGVD 29
 Elevations

Wayah Gap, 2.0 mi. W. of, 5.2 mi. E. of Aquone,
 15 ft. N. of center line of rd., at small drain crossing,
 in sandstone outcrop; 1-in. square cut 3,793.85

Wayah Gap, 2.4 mi. W. of, 4.7 mi. E. of Aquone,
 12 ft. N. of center line of highway, at small drain,
 6 ft. E. of stream, on rock outcrop; chiseled square,
 painted "U.S. 3670.0 B.M." 3,671.95

Wayah Gap, 3.0 mi. W. of, 4.1 mi. E. of Aquone,
 30 ft. W. of intersection of logging rd., at log
 landing, in root on N. side of 8-in. chestnut tree;
 copper nail and washer, painted "U.S. 3458.8 B.M." 3,460.69

Wayah Gap, 3.5 mi. W. of, 3.7 mi. E. of Aquone, 45 ft.
 E. of intersection of T-rd. NE., at sharp curve in
 main rd., 60 ft. E. of drain crossing, 20 ft. S. of
 center line of T rd., 40 ft. S. of stream, in
 concrete post; standard tablet stamped "K 7 1934"
 painted "U.S. 3342.8 P.B.M." 3,344.616-

Reference mark, 90 ft. W. of tablet, 45 ft. SW. of
 rd., intersection, in root on N. side of 24-in.
 hemlock tree; copper nail and washer, painted
 "U.S. 3330.6 R.B.M." 3,332.49

Wayah Gap, 4.1 mi. W. of, 3 mi. E. of Aquone, 17 ft.
 W. of SW. corner of house, 40 ft. N. of center line of
 rd., inroot on SW. side of 24-in. walnut tree; copper
 nail and washer, painted U.S. 3342.6 B.M." 3,244.40

Aquone, 2.1 mi. E. of, about 600 ft. S. of C.C.C.
 camp, 35 ft. N. and 27 ft. W. of T-rd. N. to camp,
 40 ft. NW. of signpost "Camp Winfield Scott," in
 root on S. side of 12-in. cedar tree; copper nail and
 washer; painted "U.S. 3012.6 B.M." 3,014.55

Aquone, 1.6 mi. E. of, 60 ft. N. and 10 ft. W.
 of wooden bridge over Jarrett Creek, 20 ft. NE. of
 center line of rd., in root on W. side of 12-in.
 apple tree; copper nail and washer, painted "U.S.
 2923.9 B.M." 2,925.84

Aquone, 1.1 mi. E. of, 80 ft. S. of rd. fork W.,
 20 ft. E. of NE. corner of old residence, 3 ft. W.
 of garden fence, 6 ft. S. of gate, in E. edge of
 yard, in concrete post; standard tablet stamped
 "K 8 1934" 2,906.811

QUAD. WAYAH BALD

STATE N.C.

By R.P. Willingham, 1936

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

ADJ. 1929 General

BK. D6908

Recopy

10/11/49 CMR

-4-

NGVD 29
Elevations

Reference mark, 135 ft. NW. of tablet, at NW. corner of yard, in root on N. side of 30-in. white pine tree; copper nail and washer	2,901.66
Aquone, 1,200 ft. SE. of post office, 120 ft. SW. of W. end of bridge over Nantahala River, 100 ft. S. of rd. crossing R.R., 70 ft. W. of center line of R.R., 30 ft. N. of SE. corner of cemetery fence, in concrete post; standard tablet stamped "K 9 1934," painted "U.S. 2864.8 P.B.M." (R.M.'s below)	2,866.689
Reference mark, 1, 65 ft. SE. of tablet, 30 ft. W. of R.R., in root on W. side of 12-in. oak tree; copper nail and washer	2,855.71
Reference mark 2, 30 ft. N. of tablet, on bank on S. side of rd., in root on W. side of 30-in. oak tree; copper nail and washer	2,861.74
Aquone, 0.2 mi. NW. of post office, 80 ft. W. of T-rd. W., 10 ft. NE. of stream crossing, 12 ft. W. of center line of T-rd., in root on S. side of 20-in. oak tree; copper nail and washer, painted "U.S. 2877.3 B.M."	2,879.202
Aquone, 1.1 mi. W. of, 60 ft. NE. of R.R. crossing, 30 ft. N. of center line of tracks, 30 ft. S. of highway, in root on E. side of 10-in. oak tree; copper nail and washer painted "U.S. 2960.2 B.M."	2,960.69
Aquone, 2.2 mi. W. of, 100 ft. S. and 30 ft. W. of R.R. crossing, 95 ft. S. of rd. fork, (rd. S. to Hayesville, W. to Andrews, east to Franklin), at E. edge of rock quarry, in rock outcrop; standard tablet stamped "R W 2 1936"	3,064.308
Reference mark, 65 ft. NW. of tablet, 40 ft. S. of rd., in root on E. side of cherry tree; copper nail and washer, painted "U.S.R.B.M. 3063.3"	3,064.82
Aquone, 2.2 mi. W. of, P.B.M. K 36 (not tied by Willingham) not described	3,066.785
Reference mark (not described)	3,063.74

QUAD. WAYAH BALD

STATE N.C.

By

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

ADJ. 1929 General

BK. B6908

Recopy

10/11/49 CMR

-5-

	NGVD 29 Elevations
Aquone, 2.8 mi. W. of, 75 ft. W. and 30 ft. S. of wooden bridge over Chega Creek, 30 ft. S. of center line of rd., on W. bank of stream, in root on E. side of 20-in. hemlock tree; copper nail and washer, painted "U.S. 3198.2 B.M."	3,198.51
Aquone, 4 mi. W. of, in old Road Gap, 40 ft. N. of rd., opposite trail to Tuscutta Bald, 15 ft. above level of highway, in root on S. side of 14-in. oak tree; copper nail and washer, painted "U.S. 3499.5 B.M."	3,499.83
Andrews, 6.3 mi. E. of, 55 ft. W. of rd. fork, 90 ft. W. of wooden bridge over Junaluska Creek, 130 ft. W. of R.R. crossing, 35 ft. NE. of NE. corner of J.H. Hicks residence, in rock ledge; standard tablet stamped "K 12 1936"	2,895.988
FROM AQUONE, NORTHWEST AND SOUTHWEST ALONG ROADS BY WAY OF JUNALUSKA GAP TO NEAR CENTER OF WEST BORDER OF QUADRANGLE (by R.P. Willingham in 1936)	
Aquone, 0.7 mi. NW. of, 2.2 mi. SE. of Morgan Cut, 30 ft. W. of center line of rd., in root on E. side of 14-in. balsam tree; copper nail and washer, painted "U.S. 2957.2 B.M."	2,959.18
Aquone, 1.0 mi. NW. of, 1.9 mi. SE. of Morgan Cut, 25 ft. E. of center line of rd., in root on W. side of 6-in. oak tree; copper nail and washer, painted "U.S. 3113.1 B.M."	3,115.08
Aquone, 1.7 mi. NW. of, 1.3 mi. SE. of Morgan Cut, 125 ft. N. of residence, 50 ft. NE. of rd., in root on W. side of 14-in. water oak tree; copper nail and washer, painted "U.S. 3181.2 B.M."	3,183.27
Aquone, 2.1 mi. NW. of, 3.7 mi. SE. of Morgan Cut, 20 ft. W. of center line of rd., in root on W. side of 30-in. oak tree; copper nail and washer, painted "U.S. 3295.3 B.M."	3,297.39
Aquone, 2.9 mi. NW. of, at Morgan Cut, 140 ft. NE. of rd. fork, 10 ft. S. of rdigo rd., in concrete post; standard tablet stamped "K 10 1934", painted "U.S. 3604.7 P.B.M."	3,606.698
Reference mark, 1, 40 ft. NE. of tablet, in root on S. side of 30- XI inch oak tree; copper nail and washer	3,605.52

QUAD. WAYAH BALD

STATE N.C.

By

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

ADJ. 1929 General

Ek. B6908

Recopy

10/11/49 CMR

-6-

NGVD 29
Elevations

Reference mark 2, 40 ft. SW. of tablet, in root on S. side of 30-in. chestnut tree; copper nail and washer	3,603.70
Morgan Cut, 1.2 mi. SW. of, 15 ft. S. of small wooden culvert, at drain crossing, at sharp curve in rd., on top of rock outcrop; chiseled square	3,605.74
Morgan Cut, 1.8 mi. SW. of, about 400 ft. S. of Valley River Gap, 25 ft. NW. of center line of rd., in sandstone boulder; standard tablet stamped "K 11 1934"	3,505.860
Reference mark, 120 ft. NE. of tablet, 30 ft. E. of center line of rd., in root on S. side of 30-in. oak tree; copper nail and washer, painted "U.S. 3510.9 R.B.M."	3,512.88
Morgan Cut, 2.8 mi. SW. of, in angle at point where R.R. bears E. from rd., 10 ft. SE. of center line of rd., on bank, in root on N. side of 14-in. maple tree; copper nail and washer	3,211.30
Morgan Cut, 3.2 mi. SW. of, 25 ft. SW. of SW corner of barn, 15 ft. N. of center line of rd., in root on S. side of 6-in. pine tree; copper nail and washer, painted "U.S. 3038.9 B.M."	3,040.88
64	
FROM BUCK CREEK CAMP ON HIGHWAY TO NORTHWEST ALONG ROAD AND RAILROAD TO QUONS (by R.P. Willingham in 1936)	
C.C.C. Camp F-12, 1.7 mi. N. of, on Buck Creek Road, 120 ft. S. of culvert, 15 ft. W. of center line of rd., on sandstone ledge; chiseled square	3,277.10
C.C.C. Camp F-12, 2.6 mi. N. of, on Buck Creek Road, 30 ft. N. of Y rd. fork, at base of ledge on boulder; chiseled square	3,226.31
C.C.C. Camp F-12, 2.8 mi. N. of, on Buck Creek Road, 40 ft. W. of center line of rd., in pignen, in E. side of 12-in. birch tree; copper nail and washer, painted "U.S. 3217.2 B.M."	3,218.73
C.C.C. Camp F-12, 4.1 mi. N. of, 20 ft. N. of old R.R. bed, on top of bank, in N. EEM root of 16-in. maple tree; copper nail and washer, painted "U.S. 3102.8 B.M."	3,164.27

QUAD. WAYAH BALD

STATE N.C.

By R.P. Willingham, 1935

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

ADJ. 1929 General

Bk. B6908

Recopy

10/11/49 CMR

-7-

NGVD 29
Elevations

C.C.C. Camp F-12, 5.3 mi. N. of, 320 ft. S. of R.R. crossing, 30 ft. E. of old R.R. bed, 50 ft. W. of W. bank of Nantshala River, in concrete post; standard tablet stamped "K 37 1934" painted "U.S. 3080.7 P.B.M."	3,082.193
Reference mark, 40 ft. E. of tablet, in root on W. side of 14-in. birch tree; copper nail and washer, painted "U.S. 3079.5 B.M."	3,081.00
Aquone, 7.9 mi. S. of, by way of R.R., 30 ft. E. of R.R., in root on NE. side of 14-in. beech tree; copper nail and washer, painted "U.S. 3053.1 B.M."	3,054.63
Aquone, 6.9 mi. S. of by R.R., about 700 ft. N. of siding, 20 ft. E. of center line of track, in root on W. side of 12-in. apple tree; copper nail and washer, painted "U.S. 3030.9 B.M."	3,032.06
Aquone, 6.0 mi. S. of by rail, 25 ft. N. of center line of track, in concrete post; standard tablet stamped "K 38 1934" painted "U.S. 3000.7 P.B.M."	3,021.603
Reference mark, 200 ft. SW. of tablet, 15 ft. S. of center line of track, in N. base of 30-in. oak tree; copper nail and washer, painted "U.S. 3020.9 R.B.M."	3,022.07
Aquone, 5.1 mi. S. of by rail, 12 ft. N. of center line of tracks, in trunk on S. side of 20-in. birch tree; copper nail and washer; painted "U.S. 3000.3 B.M."	3,001.49
Aquone, 4.1 mi. S. of, by rail, 2 ft. N. of N. rail, 6 inches below base of rail, at foot of ledge on rock; chiseled square	2,981.48
Aquone, 3.4 mi. S. of by rail, at small clearing and loop in R.R., 20 ft. W. of center line of tracks, in concrete post; standard tablet stamped "K 39 1934" painted "U.S. 2947.1 P.B.M."	2,948.176
Reference mark, 90 ft. NE. of tablet, in NE. root of 20-in. oak tree; copper nail and washer, painted "U.S. 2948.7 R.B.M."	2,949.85
Aquone, 2.2 mi. S. of by rail, 45 ft. S. of center line of trestle over Clear Creek, 35 ft. SW. of center line of tracks, in root on N. side of double birch tree; copper nail and washer, painted "U.S. 2905.0 B.M."	2,905.42

QUAD. WAYAH BALD

STATE N.C.

By

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

ADJ. 1929 General

EK. B6908

Recopy

10/11/49 CMR

-8-

NGVD 29
Elevations

Aquone, 1.4 mi. S. of by rail, 400 ft. N. of rd. crossing,
at R.R. switch, 25 ft. SW. of drain crossing, 8 ft.
NW. of center line of tracks, on lower portion of
ledge; chiseled square

2,889.52

Aquone, 1.1 mi. S. of by rail, 35 ft. E. of center
line of tracks, in root on S. side of 20-in. buckeye
tree; copper nail and washer, painted "U.S. 2858.1 B.M."

2,869.20

FROM WALLACE GAP, SOUTH AND NORTHWEST ALONG ROADS BY WAY
OF STANDING INDIAN TO A POINT 0.3 MILE EAST OF BUCK CREEK
CAMP (by R.P. Willingham in 1936)

Wallace Gap, 1.2 mi. S. of, 40 ft. NW. of center line
of rd., in root on E. side of 14-in. oak tree; copper
nail washer, painted "U.S. 3578.1"

3,579.14

Wallace Gap, 2.1 mi. S. of, 50 ft. SW. of rd. forks,
12 ft. W. of center line of rd., in E. base of 20-in.
oak tree; copper nail and washer, painted "U.S. 3412.6
B.M."

3,413.59

Wallace Gap, 2.3 mi. S. of by rd. thence 0.8 mi. SE.
by rail, on W. side of R.R. bed, in rock outcrop;
standard tablet stamped "K 40 1934", painted "U.S.
3438.1 F.B.M."

3,439.675

Reference mark, 80 ft. S. of tablet, on SE. side of
tracks, on root on NW. side of 10-in. pine tree;
copper nail and washer

3,430.32

Wallace Gap, 2.3 mi. S. by rd. thence 1.9 mi. SE. by
R.R., 20 ft. W. of center line of tracks, in root on E.
side of 20-in. buckeye tree; copper nail and washer,
painted "U.S. 3479.5 B.M."

3,480.45

Wallace Gap, 2.3 mi. S. of by rd., thence 2.8 mi.
SE. by R.R., at old logging camp, 400 ft. SE. of R.R.
forks, at mouth of Big Indian Creek, on E. side of
stream, in root on E. side of 14-in. birch tree;
copper nail and washer, painted "U.S. 3517.3 B.M."

3,518.24

Kilby Gap, 0.6 mi. N. of, on E. edge of creek, on
lower portion of large boulder; chiseled square

3,712.84

ORDER THIRD
Ek.B6908
Recopy
10/11/49 CMR

ADJ. 1929 General

NGVD 29
Elevations

-9-

- Kilby Gap, 0.5 mi. N. of, 0.35 mi. S. of old lumber camp, on E. side of trail and stream, in top of boulder; standard tablet stamped "K 41 1934" 3,823.075
- Reference mark, 30 ft. N. of tablet, on E. side of trail, in root on N. side of 30-in. birch tree; copper nail and washer, painted "U.S. 3821.8 R.B.M." 3,822.84
- Kilby Gap, on E. edge of trail, on crest of ridge, in root on W. side of 18-in. oak tree; copper nail and washer, painted "U.S. 4193.3 B.M." 4,194.31
- Standing Indian Fire Tower, 1.8 mi. SE. of, on W. edge of trail, in root on E. side of twin chestnut tree; copper nail and washer 4,985.82
- Standing Indian Fire Tower, 1.6 mi. SE. of, 20 ft. S. of trail, in root on SW. side of 16-in. oak tree; copper nail and washer, painted "U.S. 5075.2 B.M." 5,076.49
- Standing Indian Fire Tower, 0.7 mi. SE. of, 12 ft. W. of trail, on ledge of rock; chiseled square, painted "U.S. 5249.5 B.M." 5,250.64
- Standing Indian Fire Tower, on summit of mountain, 30 ft. S. of SE. corner of tower, in rock outcrop; standard tablet stamped "K-43 1934", painted "U.S. 5498.2 P.B.M." (Tied by NGS, 1975) 5,499.533
- Reference mark, 8 ft. N. of N. side of tower, in rock outcrop; standard U.S.C. & G.S. disk stamped "Standing Indian Sta. 1933" 5,499.410
- Standing Indian Fire Tower, 1.0 mi. NW. of, 25 ft. NW. of switchback in trail, 15 ft. N. of trail, in root on N. side of 24-in. maple tree; copper nail and washer, painted "U.S. 4930.3 B.M." 4,931.53
- Standing Indian Fire Tower, 2.3 mi. W. of, in Deep Gap, 100 ft. NE. of end of rd., 20 ft. E. of 48-in. oak tree; in concrete post; standard tablet stamped "K 44 1934," painted "U.S. 4339.2 P.B.M." 4,340.92
- Reference mark, 110 ft. NW. of tablet, in SW. base of 40-in. oak tree; copper nail and washer, painted "U.S. 4330.0 R.B.M." 4,329.88

QUAD.	WAYAH EALD	STATE	N.C.	By	ALTITUDE ABOVE MEAN SEA LEVEL (Feet)
ORDER	THIRD	ADJ.	1929 General		
	HR. B6908-09				
	Recopy				NGVD 29 Elevations
	10/11/49 CNR		-10-		

Deep Gap, 1.1 mi. N. of, 25 ft. NE. of center line of rd., at curve, in root on E. side of 14-in. gum tree; copper nail and washer, painted "U.S. 4152.3 B.M." 4,153.38

Deep Gap, 2.5 mi. NW. of, in Park Gap, 70 ft. NE. of center line of rd., in concrete post; standard tablet stamped "K 45 1934", painted U.S. 4182.3 P.B.M." 4,183.403

Reference mark, 70 ft. W. of tablet, in root on E. side of 16-in. oak tree; copper nail and washer 4,183.90

C.C.C. Camp F-12, 2.0 mi. SE. of, 1.0 mi. W. of Park Gap, 20 ft. N. of rd., in root on S. side of 30-in. birch tree; copper nail and washer, painted "U.S. 3721.6 B.M." 3,722.70

C.C.C. Camp F-12, 0.8 mi. SE. of, 15 ft. W. of center line of rd., 200 ft. SW. of wooden bridge, in root on E. side of 12-in. oak tree; copper nail and washer, painted U.S. 3523.0 B.M." 3,523.96 -

FROM CULLACAJA QUADRANGLE WEST AND SOUTHWEST ALONG ROADS BY WAY OF BURNINGTOWN GAP AND KYLE TO AUCHOE (by R.P. Willingham in 1936)

Oakdale Church, 40 ft. NE. of SE. cor. of church, 35 ft. E. of NE. cor., 50 ft. N. of c.l. of rd., in conc. post projecting 12 inches above ground; std. tablet stamped "K 26 1934", painted U.S. 2,199.6 B.M." 2,200.584

Reference mark, 250 ft. E. of tablet, in NE. cor. of school yard, in root on W. side of 24-in. oak tree; copper nail and washer, painted "U.S. 2,194.2 R.B.M." 2,195.18

Oakdale Church, 1.7 mi. E. of, 20 ft. NW. of NW. corner of log cabin, 70 ft. S. of center line of rd., in top of boulder; standard tablet stamped "K 27 1934" painted U.S. 2415.5 P.B.M." 2,416.572

Reference mark, 50 ft. NE. of tablet, in root on E. side of 6-in. oak tree; copper nail and washer painted "U.S. 2412.4 R.B.M." 2,413.34

Burningtown Gap, 1.8 mi. E. of, 10 ft. S. of center line of old rd., in root on E. side of 15-1/2 inch oak tree; copper nail and washer, painted "U.S. 2758.9 B.M." 2,760.15

QUAD. WYAH BALD

STATE N.C.

By R.P. Willingham
ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

1929
ADJ. 1858 General

Pk. D6909

Recopy

10/11/49 CRR

-11-

NGVD 29
Elevations~~XXXXXXXXXX~~

- Burningtown Gap, 1.3 mi. E. of, 30 ft. N. of center line of old rd., 12 ft. above level of rd., in root on S. side of 8-in. chestnut oak tree; copper nail and washer, painted "U.S. 3123.8 B.M." 3,125.98
- Burningtown Gap, 0.7 mi. E. of, 30 ft. N. of center line of old rd. at curve, in root on S. side of 8-in. hickory tree; copper nail and washer, painted "U.S. 3005.9 B.M." 3,608.14
- Burningtown Gap, 420 ft. NW. of, 3.5 mi. E. of Kyle, 60 ft. S. of woods line, on SW. slope of ridge, in top of large white boulder; standard tablet stamped "K 28 1934" painted "U.S. 4233.2 P.B.M." 4,235.724
- Reference mark, 440 ft. SE. of tablet, in gap, 60 ft. S. of rd., in root on NW. side of 30-in. oak tree; copper nail and washer, painted "U.S. 4208.3 R.B.M." 4,210.78
- Kyle, 2.4 mi. E. of, 1.1 mi. N. of Burningtown Gap, 25 ft. N. of center line of rd., in root on S. side of 20-in. oak tree; copper nail and washer 3,851.00
- Kyle, 2.0 mi. E. of, 100 ft. S. of log landing, 25 ft. N. of center line of rd., in root on S. side of 24-in. oak tree; copper nail and washer, painted "U.S. 3702.9 B.M." 3,705.08
- Kyle, 1.0 mi. E. of, 100 ft. W. of wooden bridge over stream crossing, 35 ft. S. of center line of rd., in root on S. side of 18-in. oak tree; copper nail and washer, painted "U.S. 3305.7" 3,307.71
- Kyle, 60 ft. W. of T-rd. E. to Burningtown Gap, 80 ft. W. of wooden bridge, 50 ft. W. of center line of rd., in top of sharp rock outcrop; standard tablet stamped "K 29 1934" painted "U.S. 3214.6 P.B.M." 3,216.399
- Reference mark, 80 ft. NE. of tablet, 20 ft. E. of center line of rd., on top of sharp rock; chiseled square, painted "U.S. 3212.2 R.B.M." 3,214.37
- Kyle, 1.1 mi. SW. of, 3.8 mi. NE. of Aquone, about 200 ft. W. of residence of Mrs. Wood, 20 ft. W. of center line of rd., in root on W. side of 20-in. oak tree; copper nail and washer, painted "U.S. 3378.6 B.M." 3,380.53

QUAD. WAYAH BALD

STATE N.C.

By

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)ORDER THIRD
EX. 116909

Adj. 1929 General

Recopy

10/11/49 CMR

-12-

NGVD 29
Elevations

- Aquone, 3.0 mi. NE. of, 100 ft. W. of residence,
30 ft. N. of center line of rd., in root on SE. side
of maple tree; copper nail and washer, painted
"U.S. 3212.6 B.M." 3,214.55
- Aquone, 2.6 mi. NE. of, 70 ft. NE. of NE. corner of
house, 25 ft. W. of center line of rd., in root
on W. side of 14-in. apple tree; copper nail and
washer, painted "U.S. 3042.5 B.M." 3,044.39
- Aquone, 2.2 mi. NE. of, 60 ft. SW. of T-rd. intersection,
on E. brow of ridge, 6 ft. W. of W. edge of cut, in
concrete post; standard tablet stamped "K 30 1934",
painted "U.S. 3001.6 P.B.M." 3,003.438
- Reference mark, 15 ft. E. of tablet, in root on W. side
of 10-in. oak tree; copper nail and washer, painted
"U.S. 2998.2 R.B.M." 3,000.05
- Aquone, 1.7 mi. NE. of, 45 ft. N. of rd. fork, 90 ft.
N. of wooden bridge, 30 ft. W. of center line of
rd., in root on SW. side of 30-in. oak tree; copper
nail and washer, painted "U.S. 2817.8 B.M." 2,819.57
- Aquone, 0.7 mi. NE. of, 180 ft. N. of wooden bridge over
Rocky Branch, at bend in rd., 60 ft. W. of center
line of rd., in root on W. side of 30-in. oak tree;
copper nail and washer, painted "U.S. 2841.0 B.M." 2,842.84
- FROM CULLASAJA QUADRANGLE SOUTHWEST ALONG HIGHWAY 64
INTO BIG STAMP KNOB QUADRANGLE (by R.P. Willingham in
1936)
- Franklin, 11.8 mi. SW. of, on Highway 64, 15 ft. NE.
of NE. corner of residence of Lester Waldroop,
50 ft. S. of center line of highway, in concrete
post; standard tablet stamped "K 15 1934" painted
"U.S. 2685.8 P.B.M." 2,686.463
- Reference mark, 0.2 mi. NW. of tablet, 15 ft. N.
of center line of highway, on W. end of concrete
head wall; chiseled square 2,751.02
- Franklin, 12.5 mi. SW. of, on U.S. Highway 64, 120 ft.
N. of house, 20 ft. W. of center line of highway, 12
ft. above level of rd., in root on SE. side of
twin poplar tree; copper nail and washer, painted
"U.S. 2903.9 B.M." 2,904.68

QUAD. WAYAH BALD

STATE N.C.

By

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

Adj. 1929 General

Bl. B6909

Recopy

10/11/49 CMR

-13-

NGVD 29
Elevations

Franklin, 12.8 mi. SW. of, on Highway 64, 1.8 mi. E.
of Wallace Gap, 70 ft. S. of Byrd's Gap store, 40 ft.
W. of center line of rd., in root on S. side of
20-in. oak tree; copper nail and washer, painted
"U.S. 3009.7 B.M." 3,010.55

Wallace Gap, 1.3 mi. E. of, on Highway 64, at Big Horseshoe
Bend, 12 ft. S. of center line of highway, on E. end of
head wall of concrete culvert; chiseled square, painted
"U.S. 3199.0 B.M." 3,199.96

Wallace Gap, 0.8 mi. E. of, on Highway 64, 12 ft. W. of
center line of rd., on S. end of concrete head wall;
chiseled square, painted "U.S. 3420.1 B.M." 3,421.07

Rainbow Springs, 2.6 mi. E. of, on Highway 64, in
Wallace Gap, 50 ft. SW. of rd. fork, on W. side of
gap, in concrete post; standard tablet stamped "K 16
1934" painted "U.S. 3736.7 P.B.M." 3,737.737
RECOVERED
4-66
WASH. D.C. 7/12/45

Reference mark, 40 ft. N. of tablet, 40 ft. SW.
of center line of rd., in root on N. side of 14-in.
oak tree; copper nail and washer 3,730.97

Rainbow Springs, 2.1 mi. E. of, on Highway 64, 40 ft.
NE. of center line of highway, in root on SW. side
of 10-11 inch oak tree; copper nail and washer, painted
"U.S. 3560.8 B.M." 3,561.83

Rainbow Springs, 1.6 mi. E. of, on Highway 64, 40 ft.
NW. of center line of highway, in root on W. side
of 12-in. oak tree; copper nail and washer, painted
"U.S. 3439.1 B.M." 3,439.98

Rainbow Springs, 1.1 mi. E. of, on Highway 64, 70 ft.
S. of residence, 50 ft. W. of SW. corner of old
store building, 5 ft. NW. of fence, 40 ft. N. of
center line of highway, in root on S. side of 24-in.
oak tree; copper nail and washer, painted "U.S. 3333.8
B.M." 3,434.70

Rainbow Springs, 0.7 mi. E. of, on highway 64, 18 ft.
NE. of NE. corner of cabin, 15 ft. W. of center
line of highway, in root on SW. side of 36-in. oak tree;
copper nail and washer, painted "U.S. 3326.2 B.M." 3,327.15

QUAD. WAYAH BALD

STATE NC.

By

ALTITUDE ABOVE
MEAN SEA LEVEL
(Foot)

ORDER THIRD

Adj. 1929 General

BK. 26909

Ready

10/11/49 CMR

-14-

NGVD 29
Elevations

- Rainbow Springs, 0.4 mi. W. of post office, on highway 64, 210 ft. NE of bridge over Black Creek, at curve in rd., 30 ft. S. of center line of highway, in concrete post; standard tablet stamped "K 17 1934," painted "U.S. 3295.3 B.M." 3,296.172
- Reference mark, 160 ft. S. of tablet, 30 ft. E. of center line of highway, in root on S. side of 30-in. oak tree; copper nail and washer, painted "U.S. 3299.1 B.B.M." 3,299.98
- Rainbow Springs, 1.0 mi. W. of, on Highway 64, opposite Ritter Lumber Company's stables, 40 ft. N. of center line of highway, in root on S. side of 6-in. oak tree; copper nail and washer, painted "U.S. 3444.6 B.M." 3,445.53
- Rainbow Springs, 2.0 mi. W. of, in Black Gap, 50 ft. S. of Macon-Clay County line, 50 ft. W. of center line of Highway 64, in root on W. side of 20-in. oak tree; copper nail and washer, painted "U.S. 3841.9 B.M." 3,843.45
- Rainbow Springs, 2.8 mi. W. of, 20 ft. E. of masonry head wall, 50 ft. SE. of center line of Highway 64, in root on W. side of 8-in. ash tree; copper nail and washer, painted "U.S. 3579.5 B.M." 3,581.00
- Rainbow Springs, 3.3 mi. W. of, 0.3 mi. E. of Buck Creek C.C.C. Camp, 150 ft. W. of W. end of bridge over Buck Creek, 100 ft. S. of center line of Highway 64, in top of concrete post; standard tablet stamped "R 18 1934" painted "U.S. 3465.8 P.B.M." 3,467.261
- Reference mark, 60 ft. NW. of tablet, in root on NW. side of 36-in. oak tree; copper nail and washer, painted "U.S. 3466.7 R.B.M." 3,468.17
- Rainbow Springs, 3.9 mi. W. of, 0.3 mi. W. of C.C.C. Camp, 40 ft. N. of center line of Highway 64, in root on E. side of 12-X inch oak tree; copper nail and washer, painted "U.S. 3409.4 B.M." 3,410.89
- Rainbow Springs, 4.3 mi. W. of, 340 ft. W. of rd. fork, 260 ft. W. of W. end of bridge over Buck Creek, 25 ft. N. of center line of Highway 64, in root on E. side of 24-in. birch tree; copper nail and washer, painted "U.S. 3350.5 B.M." 3,351.99

QUAD. WAYAH BALD

STATE N.C.

By

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

ADV. 1929 General

EX. 18909

Recopy

10/12/49 CMR

-15-

NGVD 29
Elevations

RAINBOW Springs, 4.8 mi. W. of, 1.2 mi. W. of C.C.C.
Camp, 15 ft. S. of center line of Highway 64, on E.
end of masonry head wall; chiseled square, painted
"U.S. 3578.6 B.M."

3,380.12

Rainbow Springs, 5.4 mi. W. of, 0.5 mi. E. of Glade
Gap, 35 ft. E. of center line of Highway 64, in
root on S. side of 20-in. birch tree; copper nail and
washer, painted "U.S. 3514.7"

3,516.03

Rainbow Springs, 5.9 mi. W. of, in Glade Gap, 60 ft.
SW. of center line of Highway 64, at elevation sign,
in concrete post; standard tablet stamped "K 19 1934"
painted "U.S. 3677.3 B.M."

3,678.692

Reference mark, 50 ft. S. of tablet, in root on SE.
side of 20-in. hickory tree; copper nail and washer,
painted "U.S. 3673.3 B.M."

3,674.65

Rainbow Springs, 6.5 mi. W. of, 0.6 mi. SW. of
Glade Gap, 50 ft. NE. of center line of Highway 64,
in root on W. side of 20-in. oak tree; copper nail
and washer, painted "U.S. 3481.8 B.M."

3,463.15

Rainbow Springs, 7.1 mi. W. of, 1.2 mi. W. of Glade
Gap, 55 ft. NW. of center line of Highway 64, in root
on W. side of 20-in. oak tree; copper nail and washer,
painted "U.S. 3251.4 B.M."

3,252.70

Rainbow Springs, 7.5 mi. W. of, 15.1 mi. E. of
Hayesville, 150 ft. NW. of concrete culvert at S.
end of horseshoe curve, 70 ft. N. of center line of
Highway 64, in root on E. side of 30-in. hickory
tree; copper nail and washer, painted "U.S. 3070.1 B.M."

3,071.28

Hayesville, 14.6 mi. E. of, 50 ft. NE. of culvert,
50 ft. N. of center line of Highway 64, in root on
E. side of 18-in. poplar tree; copper nail and
washer, painted "U.S. 2900.6 B.M."

2,901.79

Hayesville, 13.5 mi. E. of, 150 ft. W. of deep cut,
50 ft. N. of center line of Highway 64, in root on
SE. side of 30-in. hickory tree; copper nail and
washer, painted "U.S. 2519.8 B.M."

2,520.94

Hayesville, 13.1 mi. E. of, 70 ft. W. of center
line of Highway 64, in root on NE. side of 10-in.
sourwood tree; copper nail and washer, painted
"U.S. 2363.4 B.M."

2,364.46

QUAD. WAYAH BALD

STATE H.C.

Br

ALTITUDE ABOVE
MEAN SEA LEVEL
(Foot)

ORDER THIRD

Adj. 1929 General

Bk. B6909

Recopy

10/12/49 CMR

-16-

NGVD 29
Elevations

- Hayesville, 12.7 mi. E. of, 130 ft. NE. of wooden Highway bridge over Mill Creek, 100 ft. E. of water mill, 60 ft. NW. of center line of Highway 64, in concrete post; standard tablet stamped "K 20 1934," painted "U.S. 2207.6 P.B.N." 2,208.666
- Reference mark, 35 ft. W. of tablet, in root on NE. side of 20-in. Walnut tree; copper nail and washer, painted "U.S. 2202.7 R.B.N." 2,203.73
- Hayesville, 12.1 mi. E. of, 15 ft. S. of center line of Highway 64, on NE. corner of masonry head wall; chiseled square, painted "U.S. 2139.7 B.N." 2,140.72
- Hayesville, 11.5 mi. E. of, 100 ft. W. of tourist home, 40 ft. N. of cabin, 12 ft. SE. of center line of Highway 64, on NE. end of concrete head wall; chiseled square, painted "U.S. 2102.1 B.N." 2,103.22
- Hayesville, 11.0 mi. E. of, 30 ft. N. of center line of Highway 64, 20 ft. S. of stream, in root on E. side of 36-in. oak tree; copper nail and washer, painted "U.S. 2052.8 B.N." 2,053.83
- Hayesville, 10.5 mi. E. of, 0.2 mi. W. of Shooting Creek, post office, 120 ft. W. of Robert Leadford's store, 12 ft. N. of center line of Highway 64, on W. end of masonry head wall; chiseled square, painted "U.S. 2119.6 B.N." 2,120.74
- Hayesville, 10.1 mi. E. of, 0.6 mi. W. of Shooting Creek post office, 70 ft. NE. of old store, 30 ft. S. of residence, in root on SE. side of 24-in. white pine tree; copper nail and washer, painted "U.S. 2051.4 B.N." 2,052.59
- Hayesville, 9.5 mi. E. of, 180 ft. E. of T-rd. N., 140 ft. E. of Paul Moody's mail box, 20 ft. S. of center line of Highway 64, in rock ledge; standard tablet stamped "K 21 1934" 2,004.610
- Reference mark, 150 ft. W. of tablet, 40 ft. S. of rd., on fence line, in root on NW. side of 10-in. oak tree; copper nail and washer 2,007.07

QUAD. WAYAH BALD

STATE N.C.

By

ALTITUDE ABOVE
MEAN SEA LEVEL
(Feet)

ORDER THIRD

Adj. 1929 General

Bk. B0909

Recopy

10/12/49 CNR

-17-

NGVD 29
Elevations.

- Hayesville, 3.6 mi. E. of, at crest of low ridge,
25 ft. E. of residence, 20 ft. N. of center line of
Highway 64, in root on E. side of 30-in. oak tree;
copper nail and washer, painted "U.S. 2026.9 B.M." 2,028.20
- Hayesville, 7.8 mi. E. of, 400 ft. N. of wooden
Highway bridge, at small store, 40 ft. N. of center
line of Highway 64, on fence line, in root on W.
side of 16-in. tree; copper nail and washer, painted
"U.S. 1901.7 B.M." 1,982.97
- Hayesville, 7.5 mi. E. of, 180 ft. SE. of T-rd. N.,
200 ft. SE. of church, 10 ft. S. of center line of
Highway 64, on SW. abutment of concrete highway
bridge over Shooting Creek; chiseled square, painted
"U.S. 1935.1 B.M." 1,936.41
- Hayesville, 6.7 mi. E. of, 40 ft. W. of center line
of highway at metal culvert, 6 ft. W. of ditch, in
root on W. side of 14-in. oak tree; copper nail and
washer, painted "U.S. 1947.9 B.M." 1,948.79
- Hayesville, 6.0 mi. E. of, 45 ft. SW. of T-rd. N. to
Aquone, at SE. corner of Ben Ledford's store, 40 ft.
S. of center line of Highway 64, in rock outcrop;
standard tablet stamped "K 22 1934" painted "U.S. 1885
P.B.M." 1,885.768
- Reference mark, 80 ft. NE. of tablet, 20 ft. N.
of center line of highway, on concrete head wall;
chiseled square, painted "U.S. 1885.9 R.B.M." 1,887.15
- FROM BIG STAMP KNOB QUADRANGLE NORTHEAST ALONG ROAD TO
A POINT 2.2 MILES WEST OF AQUONE (by R.P. Willingham, in 1936)
- Philips Store, 0.9 mi. NE. of, 80 ft. N. of Tusquittee
Methodist Church, 50 ft. N. of c.l. of rd., in conc.
post; std. tablet stamped "K 32 1934," painted
"U.S. 2,018.3 P.B.M." 2,019.364
- Ref. mk., 115 ft. S. of tablet, in root on SW. side of
16-in. walnut tree; copper nail and washer, painted
"U.S. 2,003.5 R.B.M." 2,009.55
- Philips, Store, 2.7 mi. NE. of, 80 ft. W. of old school-
house, (residence now), 40 ft. N. of center line of
rd., in root on S. side of 24-in. oak tree; copper
nail and washer, painted "U.S. 2078.8 B.M." 2,079.78

QUAD. WAYAH BALD

STATE N.C.

By R.P. Willingham, 1926
ALTITUDE ABOVE
MEAN SEA LEVEL
(Foot)

ORDER THIRD

ADJ. 1929 General

Bk. B6909

Recopy

10/22/49 CMA

-18-

NGVD 29
Elevations

- Philips store, 3.3 mi. NE. of, 100 ft. N. of inter-
section of T-rd. N to Tuni Gap, 30 ft. E. of center
line of rd., in concrete post; standard tablet stamped
"K 33 1934" painted "U.S. 2152.3 P.B.M." 2,153.270
- Reference mark, 30 ft. NW. of tablet, on flint rock;
chiseled square 2,154.62
- Tuni Gap, 4.0 mi. S. of, 25 ft. U. of center line of
rd., 10 ft. below surface of rd., in root on S. side
of 18-in. maple tree; copper nail and washer, painted
"U.S. 2313.6 B.M." 2,314.64
- Tuni Gap, 3.5 mi. S. of, at a low gap on S. side of
mountain, 12 ft. E. of center line of rd., in root
on N. side of 14-in. oak tree; wire nail and copper
washer 2,561.38
- Tuni Gap, 2.6 mi. S. of, 45 ft. NW. of intersection
of logging rd. W., 40 ft. SW. of drain crossing,
30 ft. W. of center line of rd., in top of boulder;
standard tablet stamped "K 34 1934", painted
"U.S. 2646.1 P.B.M." ~~2,647.465~~
~~2,647.465~~
- Reference mark, 50 ft. NE. of tablet, at N. edge of
drain, on N. end of boulder; chiseled square 2,641.67
- Tuni Gap, 1.7 mi. S. of, 150 ft. SE. of intersection of
old R.R. bed, 40 ft. E. of center line of rd., in
root on W. side of 12-in. poplar tree; copper nail and
washer, painted "U.S. 2906.8 B.M." 2,908.23
- Tuni Gap, 0.7 mi. S. of, 65 ft. S. of intersection
of old R.R. grade, 20 ft. S. of center line of rd., at
edge of washout, in cut in trunk of tree, 6 ft. from
ground; wire nail 3,210.94
- Tuni Gap, 40 ft. E. of center line of rd. at point
where rd. crosses top, 3 ft. above level of rd.,
in concrete post; standard tablet stamped "K 35
1934" painted "U.S. 3524.6 P.B.M." 3,526.309
- Reference mark, 50 ft. N. of tablet, in root on S. side
of 12-in. hickory tree; copper nail and washer,
painted "U.S. 3524.2 P.B.M." 3,525.88

QUAD.	WAYANBALD	STATE	N.C.	By		ALTITUDE ABOVE MEAN SEA LEVEL (Feet)
ORDER	THIRD	Adj.	1929 General			
	Pk. B6909, E7019				NGVD 29 Elevations	
	Recopy					
	10/12/49 CMR		-19-			

Tuni Gap, 1.0 mi. N. of, 40 ft. NW. of center line of rd., at drain crossing, in root on E. side of 20-in. beech tree; copper nail and washer, painted "U.S. 3220.4 B.M." 3,220.98

FROM BURTON QUADRANGLE NORTH ALONG ROAD TO A POINT 6.0 MILES EAST OF HAYESVILLE (by G.W. Moore in 1936)

Lower Bell Creek school, 3.56 mi. NE. of, 0.44 mi. N. of Low Gap, 300 ft. NE. of yellow house, 8 ft. S. of private rd. fork, in root on S. side of 14-in. hickory tree; copper nail and washer, painted "U.S.B.M. 2044.4" 2,044.38

Lower Bell Creek school, 4.25 mi. NE. of, 1.1 mi. N. of Low Pass, 50 ft. N. of group of mail boxes, 15 ft. S. of rail fence, 12 ft. E. of rd., in root on E. side of 10-in. oak tree; copper nail and washer, painted "U.S.B.M. 1996.8" 1,996.82

Lower Bell Creek school, 4.4 mi. NE. of, 1.25 mi. N. of Low Gap, 0.77 mi. S. of State Highway 28, top of hill, 46 ft. W. of rd., in pasture, top of quartzite boulder; standard tablet stamped "G W M 138 1936 2015", painted "U.S.F.B.M. 2015.0" 2,014.948

Reference mark, 25 ft. NE. of tablet, 20 ft. W. of rd., in root on NW. side of 15-in. hickory tree; copper nail and washer 2,012.47

Lower Bell Creek School, 5.02 mi. NE. of Hayesville, about 6.2 mi. SE. thence 0.05 mi. S. of center of wood bridge, 8 ft. above Shooting Creek, painted "1886.317" 1,886.31

Hayesville, about 6.15 mi. SE. of, 260 ft. W. of T-rd. S. to Low Gap, on SW. corner of W. end of S. heading of concrete culvert; chiseled square, painted "U.S. 1885.9 T.F." 1,887.19

Elev. T-rd. S. of State Highway 28, painted "1887.333" 1,887.3