

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By G.W. MOORE, 1936 ALTITUDE ABOVE MEAN SEA LEVEL (Feet)

ORDER THIRD Adj. 1929 GENERAL

BK. B7003  
RECOPY 12/8/55 lmk

NORTH CAROLINA  
BIG STAMP KNOB  
(Latitude 35°-35°15'; longitude 83°45'-84°)  
CLAY, CHEROKEE AND GRAHAM COUNTIES

NGVD 29  
Elevations

-1-

A LOOP FROM MURPHY QUADRANGLE E. AND S. ALONG HIGHWAY 64 to BRASSTOWN TRENCE SW. ALONG RD.

- Murphy, 3.0 mi. E. of, 4.0 ft. below U. S. Highway 64, on E end of S. head wall of concrete culvert over Burntwood Branch; chiseled square, painted "U.S.B.M. 1557.5" 1,537.45
- Murphy, 3.4 mi. E. of, 6.9 ft. below U. S. Highway 64, 55 ft. N. W. of T-rd. N., on W. end of N. head wall of concrete culvert over Fall Branch; chiseled square, painted "T V A B.M. 1-1-2", painted "U.S.B.M. 1559.7" 1,559.60
- Murphy, 4.0 mi. E. of, 40 ft. NW. of T-rd. NE., on N. headwall of concrete culvert; chiseled square, painted "U.S.B.M." 1,576.86
- ✓ Murphy, 4.17 mi. E. of, 0.17 mi. E. of T-rd. NE., on W. end of S. headwall of large concrete bridge culvert over Peachtree Creek; standard tablet stamped "G W M 79 1936," ~~REBETA "1989 B-SEE ATTACHMENT"~~ 1,569.193
- Reference mark, 57 ft. NE. of tablet, on E. end of N. head wall of large concrete culvert; chiseled square 1,569.11
- Murphy, 4.83 mi. E of, 0.66 mi. E. of Peach tree Creek, 0.24 mi. N.W. of Peachtree rd. forks, 85 ft. SE. of private rd. fork E., 39 ft. NE. of U.S. Highway 64, in root on W. side of 25-in. oak tree; copper nail and washer, painted "U.S.B.M. 1621.1" 1,621.01
- ✓ Murphy, 5.1 mi. E of, 670 ft. S. of Peachtree rd. fork, 14 ft. W of Mission rd. fork, on W. head wall of concrete culvert on U. S. Highway 64; standard tablet stamped "G.W.M. 83 1936 1628", painted "U.S. B.B.M. 1628.6" *NF 9/87* 1,628.460
- Reference mark, 135 ft. SE. of tablet, across rd. from store at Mission rd. forks, on E. head wall of concrete culvert on U. S. Highway 64; chiseled square 1,627.20
- Murphy, 5.75 mi. E. of, 0.65 mi. SE. of U. S Highway 64, 65 ft. SE. of junction of Mission rd. and rd. S. to Highway 64, on SW. head stone of masonry culvert; chiseled square, painted "U. S. B. M. 1676.5" 1,676.37
- Murphy, 6.4 mi. SE. of, near foot of hill, 130 ft. NE. of T-rd. NE. to Mission rd., on E. head wall of concrete culvert on U. S. Highway 64; chiseled square, painted "U.S.B.M. 1634.0" 1,633.92
- Murphy, 6.95 mi. SE. of, at concrete bridge over Hiwassee River, on NE. corner of E. parapet of N. abutment; chiseled square, painted "T V A 1 1 3" 1,598.64

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By G.W. MOORE, 1936 ALTITUDE ABOVE  
 MEAN SEA LEVEL  
 ORDER THIRD ADJ. 1929 GENERAL ADJUSTMENT (Feet)  
 BK. B7003  
 RECOPY 12/8/55 lmk CLAY, CHEROKEE AND GERARAM COUNTIES

-2-

- ✓ Murphy, 6.95 mi. SE. of, 0.7 mi. NW. of Brasstown store, on concrete highway bridge over Hiwassee River, 12 ft. W. of center line of U.S. Highway 64, 4 ft. SE. of Clay county sign, on W. parapet wall of the N. concrete abutment; standard tablet stamped "G W M 83 1936 1599", painted "U.S.P.B.M. 1,598.8" *Good 9/87* 1,598.665
- Murphy, 7.6 mi. SE. of, 240 ft. SE. of iron bridge over Brasstown Creek, at Clay-Cherokee county line, 12 ft. NE. of rd. fork W., on NE. head wall of concrete culvert on U. S. Highway 64; chiseled square, painted "U.S.B.M. 1605.82" 1,605.68
- ✓ Murphy, 7.6 mi. SE. thence 0.7 mi. SW. from, along Little Brasstown Creek rd., 14 ft. W. of T-rd. NW., 30 ft. SW. of wood bridge over Brandles Branch, 14 ft. W. of T-rd. NW., on SW. head wall of concrete culvert under side rd.; standard tablet stamped "G W M 84 1936 1615," painted "U.S.P.B.M. 1615.1" 1,615.004
- Reference mark, 40 ft. N. of tablet, in barnyard, in root on W. side of 18-in. maple tree; copper nail and washer 1,613.
- Murphy, 7.6 mi. SE. thence 1.5 mi. SW. of along Little Brasstown Creek rd., 53 ft. W. of wood bridge over Carringer's Branch, 40 ft. W. of crossroads, on side of hill, about 5 ft. above rd., in root on E. side of 25-in. oak tree; copper nail and washer, painted "U.S.B.M. 1635.9" 1,635.80
- Murphy, 7.6 mi. SE. thence 2.1 mi. SW. from, along Little Brasstown Creek rd., 140 ft. SW. of bridge over Tweed Branch, 110 ft. NE. of rd. fork N., at Mason home, 30 ft. NW. of rd., in pasture, in root on E. side of twin apple tree; copper nail and washer, painted "U.S.B.M. 1,638.7" 1,638.59
- ✓ Murphy, 7.6 mi. SE. thence 2.8 mi. SW. of along Little Brasstown Creek rd., 2.35 mi. E. of Martin Creek school, 50 ft. NE. of wood bridge over Ricks Branch, 50 ft. NW. of rd. fork, 30 ft. W. of rd., on bank 3 ft. above rd., top of marble post; standard tablet stamped "G.W.M. 85 1936 1647," painted "U.S.P.B.M. 1647.4" 1,647.274
- Reference mark, 59 ft. E. of tablet, 95 ft. E. of wood bridge over Rock Creek, 20 ft. N.E. of rd. fork N., in root on SW. side of 8-in. oak tree; copper nail and washer 1,649.15
- FROM BRASSTOWN, SE. 4.8 MI. ALONG HIGHWAY 64, THENCE NE. AND NW. ALONG RDS. TO NEAR ANDREWS DAM.
- Murphy, 8.06 mi. SE. of, 0.4 mi. SE. of Brasstown, on SW. head wall of a masonry culvert; chiseled square, painted "U.S.B.M. 1612.5" 1,612.3

QUAD. BIG STAMP KNOB	STATE NORTH CAROLINA	By G.W. MOORE, 1936	ALTITUDE ABOVE MEAN SEA LEVEL (Feet)
ORDER THIRD	Adj. 1929 GENERAL ADJUSTMENT		
BK. B7003			
REGOPY 12/8/55 lmk	CLAY, CHEROKEE AND GRAHAM COUNTIES		NGVD 29 Elevations

-3-

- Murphy, 8.5 mi. SE. of, 0.8 mi. SE. of Brasstown, 20 ft. E. of center line of U.S. Highway 64, 20 ft. NE. of NE. corner of stone building, at Mountain Valley Creamery, in base of telephone pole; spike, pole painted "B.M. T.V.A. B.T. 2" "1618.1" 1,618.01
- Murphy, 8.9 mi. SE. of, 1.25 mi. SE. of Brasstown, 87 ft. S. of rd. fork NE., 4 ft. below U. S. Highway 64, on SW. head wall of large concrete culvert over Buchanan Branch; standard tablet stamped "G W M 86 1936 1613", painted "U.S.P.B.M. 1613.2" 1,613.105
- Reference mark, 36 ft. NE. of tablet, on N. end of NE. head wall of concrete culvert; chiseled square 1,613.40
- Murphy, 9.6 mi. SE. of, 1.9 mi. SE. of Brasstown, 64 ft. S. of intersection of center line of Pine Log rd., and U.S. Highway 64, 7 ft. above floor or iron bridge over Brasstown Creek, at NW. corner of bridge, top of N. rivet of inside row; in painted circle, bridge painted "B.M. T V A B T 3" "1634.1" 1,633.90
- Murphy, 9.9 mi. SE. of, 2.2 mi. SE. of Brasstown, 25 ft. S. of U. S. Highway 64, at U bend, 6 ft. E. of Riley Ellis mailbox, top of boulder; chiseled square boulder painted "B.M. T V A B T 4," "1658.4" 1,658.25
- Murphy, 10.67 mi. SE. of, 3.0 mi. SE. of Brasstown, on concrete highway bridge over Trout Cove Branch, at N. end of W. guard; standard tablet stamped "G.W.M. 87 1936 1650," painted "U.S.P.B.M. 1605.3" 1,650.170
- Brasstown, 3 mi. SE. of, on concrete highway bridge over Trout Cove Branch, at N. end of W. guard, on SE. (outside) corner of hollow square 1,649.36
- Murphy, 11.4 mi. SE. of, 3.7 mi. SE. of Brasstown, 30 ft. NW. of junction of Trout Cove rd. and U. S. Highway 64, at top of hill, at N. end of wing wall of N. heading of masonry culvert; chiseled square, painted "U.S.B.M. 1733.7" 1,733.54
- Murphy, 11.76 mi. SE. of, 4.1 mi. SE. of Brasstown, at foot of hill, 40 ft. SE. of store, on S. head wall of concrete culvert over creek; chiseled square, painted "U.S.B.M. 1692.9" 1,692.70
- Murphy, 12.4 mi. SE. of, 4.75 mi. SW. of Brasstown, 300 ft. NW. of T-rd. NE. through Brasstown gap, 4.6 ft. below U. S. Highway 64, on N. end of E. head wall of concrete culvert over creek; standard tablet stamped "G W M 88 1936 1680," painted "U.S.P.B.M. 1680.2" 1,680.011
- Reference mark, 96 ft. NW. of tablet, on S. end of E. head wall of concrete culvert over Beach Creek, 4.1 ft. below U. S. Highway 64; chiseled square 1,680.75

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By G.W. MOORE, 1936 ALTITUDE ABOVE  
MEAN SEA LEVEL  
(Foot)

ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK. B7003

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTIES

11.

- Murphy, 12.46 mi. SE., thence 0.7 mi. NE. of, 40 ft. E. of John Telms' house, 9 ft. W. of rd., in root on SW. side of 30-in. oak tree with mailbox; copper nail and washer, painted "U.S.B.M. 1874.0" 1,873.78
- Murphy, 12.46 mi. SE. of, thence 1.46 mi. NE. from, about 200 ft. W. of Copper Hill Church, 90 ft. SW. of rd. fork, in eye of rd. forks, in root on W. side of 10-in. oak tree; copper nail and washer, painted "U.S.B.M. 1978.9" 1,978.73
- ✓ Murphy, 12.46 mi. SE. thence 2.0 mi. NE. from, 53 ft. N. of ford over creek, 25 ft. NW. of rd., top of boulder; standard tablet stamped "G W M 89 1936, 2,004." painted "U.S.P.B.M. 2003.7" 2,003.531
- Reference mark, 32 ft. SW. of tablet, 20 ft. NW. of rd., 30 ft. N. of creek crossing, in root on SE. side of 30-in., inclined, gum tree; copper nail and washer 2,000.91
- Murphy, 12.46 mi. SE. thence 2.35 mi. NE. of, at top of ridge in Brasstown gap, 23 ft. NW. of rd., in root on NW. side of 25-in. oak tree; copper nail and washer, painted "U.S.B.M. 2175.0" 2,174.79
- Murphy, 12.46 mi. SE. thence 3.0 mi. NE. from, 7.5 ft. NE. of N. side of porch of farmhouse, 20 ft. NW. of rd., 7 ft. above rd. level, in root on S. side of 25-in. oak tree; copper nail and washer, painted "U.S.B.M. 1971.6" 1,971.44
- Murphy, 12.46 mi. SE. thence 3.65 mi. NE. from at curve on point of hill, 11 ft. NE. of rd., in root on NE. side of 15-in. oak tree; copper nail and washer, painted "U.S.B.M. 1976.3" 1,976.12
- Murphy, 12.46 mi. SE. thence 4.35 mi. NE. from, 135 ft. SE. of T-rd. S., 300 ft. SE. of T-rd. NE. at Hayesville, 13 ft. S. of rd. E., in root on N. side of 15-in. maple tree; copper nail and washer, painted "U.S.B.M. 1853.8" 1,853.68
- ✓ Murphy, 10.75 mi. E. to Shallow Ford Bridge, thence 2.25 mi. SE. of, 0.5 mi. NW. of rd., fork NE. to Hayesville, about 150 ft. N. of farmhouse, 20 ft. NE. of rd., on rock outcrop; standard tablet stamped "G.W.M. 90 1936 1855", painted "U.S.P.B.M. 1854.7" 1,854.509
- Reference mark, 23 ft. N. of tablet, 24 ft. NE. of rd., on rock outcrop; chiseled square 1,849.84
- Murphy, 10.75 mi. E. to Shallow Ford Bridge, thence 1.55 mi. SE. from 100 ft. S. of center of wood bridge over Sweetwater Creek, 25 ft. W. of rd., in root on E. side of 25-in. maple tree; copper nail and washer, painted "U.S.B.M. 1787.3" 1,787.17

92

QUAD BIG STAMP KNOB

STATE NORTH CAROLINA By G.W. MOORE, 1936

ALTITUDE ABOVE  
MEAN SEA LEVEL  
(Feet)

ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK. B7003

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTIES

NGVD 29  
Elevations

-5-

- Murphy, 10.75 mi. E. to Shallow Ford bridge, thence 0.95 mi. SE. of, 20 ft. S. of T-rd. N., in root on E. side of 40-in. oak tree; copper nail and washer, painted "U.S.B.M. 1753.8" 1,753.66
- Murphy, 10.75 mi. E. to Shallow Ford bridge, thence 0.32 mi. SE. of, 23 ft. NE. of center of wood bridge over Sweetwater Creek, on rock outcrop; chiseled square painted "U.S.B.M. 1683.4" 1,683.28
- Andrews Dam, 2.1 mi. above, at mileage 108.2 on old Murphy-Hayesville rd., 150 ft. SW. of Auberry's store (abandoned), on upstream side ~~of Shallow Ford bridge~~ pier of Shallow Ford bridge over Hiwassee River, on NE. pier, top of round rivet head (U.S.E.D. 21) Rivet painted red and pier painted "B.M.T.R.S. H 21" 1,685.928
- Murphy, 10.7 mi. E. of, 200 ft. E. of NW. corner of Shallow Ford bridge over Hiwassee River, 200 ft. W. of R. R. crossing, 10 ft. N. of center line of Tennessee and North Carolina R. R., 25 ft. S. of rd., on rock outcrop about 2.3 ft. above tracks; standard tablet stamped "G W M 91 1936 1686," painted "U.S.P.B.M. 1686.1" 1,686.015
- Murphy, 9.94 mi. E. of, 0.8 mi. W. along R. R. from Shallow Ford bridge, 9 ft. NE. of R. R., 0.6 ft. above tracks, on rock outcrop; chiseled square, painted "U.S.B.M. 1682.7" 1,682.62
- Murphy, 9.30 mi. E. of, 1.45 mi. W. along R. R. from Shallow Ford bridge, 0.2 mi. SE. of Carrell Lake Dam, 7 ft. S. and 3 ft. above tracks, point of rock, painted rod; painted "T V A B.M. A. L. 3", painted "U.S.B.M. 1685.2" 1,685.09
- Murphy, 9.1 mi. E. of, 0.48 mi. E. of Andrews Dam, 13 ft. E. of center line of earth dam at Carrell Lake, on top on S. side of concrete outlet; chiseled square, painted "U.S.B.M. 1690.6" 1,690.50
- Murphy, 8.6 mi. E. of, on crest of Andrews Dam, 7.4 mi. above Lake level, 68 ft. W. of Tennessee and North Carolina R. R. tracks, at E. end of dam, over concrete arch on S. side of dam; standard tablet stamped "G.W.M. 92 1936 1665," painted "U.S.P.B.M. 1665.1" 1,665.017
- Andrews Dam, at mileage 106.1, 100 ft. SE. of power house, 6 ft. W. of Tennessee and North Carolina R. R., 7 ft. below crest, 2.5 ft. below step, in concrete hollow; chiseled square (U.S.E.D. 23) 1,658.068
- FROM A POINT ON HIGHWAY 64, 4.0 MI. E. OF MURPHY, NE. AND NW. ALONG RD. TO TOMATLA.
- Murphy, 4.0 mi. E. thence 0.5 mi. NE. from, 2 ft. NW. of rd., at top of hill, in root on SE. side of 25-in. yellow pine tree; copper nail and washer, painted "U.S.B.M. 1641.5" 1,641.47

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By G.W. MOORE, 1936 ALTITUDE ABOVE  
MEAN SEA LEVEL  
(Feet)

ORDER THIRD ADJ. 1929 GENERAL ADJUSTMENT  
BK. B7003  
RECOPY 12/8/55 lmk CLAY, CHEROKEE AND GRAHAM COUNTIES

-6-

- ✓ Murphy, 4.0 mi. E. along U. S. Highway 64, thence 1.1 mi. NE. from, on N. end of W. head wall of concrete culvert over Zimmerman Creek; standard tablet stamped "G.W.M. 80 1936 1610", painted "U.S.P.B.M. 1610.2" DEST 9/87 NEW HEADY WALL 1,610.093
- Reference mark, 20 ft. NW. of tablet, 29 ft. W. of rd., in root on E. side of 8-in. oak tree; copper nail and washer 1,609.07
- Murphy, 4.0 mi. E. thence 1.82 mi. NE. from, 0.16 mi. NE. of fork over creek, 170 ft. N. of rd. fork NW., 30 ft. SE. of rd., in root on NW. side of 18-in. oak tree; copper nail and washer; painted "U.S.B.M. 1673.9" 1,673.85
- Murphy, 4.0 mi. E. thence 2.37 mi. NE. from, 0.85 mi. NW. of Peachtree, 20 ft. SE. of T-rd. W., on E. heading of masonry culvert; copper nail and washer, painted "U.S.B.M. 1635.7" 1,635.59
- Murphy, 4.0 mi. E. thence 2.92 mi. N. from, 1.4 mi. NW. of Peachtree, 30 ft. E. of rd. at curve, in root on W. side of 25-in. white oak tree; copper nail and washer, painted "U.S.B.M. 1661.8" 1,661.70
- Murphy, 4.0 mi. E. thence 3.56 mi. N. from, at top of small rise in rd. between double rd., 9 ft. NE. of main rd., in root on S. side of 15-in. apple tree; copper nail and washer, painted "U.S.B.M. 1740.1" 1,740.06
- ✓ Murphy, 4.0 mi. E. thence 3.94 mi. N. from 2.4 mi. NW. of Peachtree, 0.1 mi. NW. of private rd. fork at top of hill, 0.5 mi. S. of T-rd. S., 10 ft. NE. of rd., on rock outcrop; standard tablet stamped "G.W.M. 81 1936 1789" painted "U.S.P.B.M. 1788.6" 1,788.473
- Reference mark, 57 ft. S. of tablet, 14 ft. SW. of rd., in root on N. side of 16-in. oak tree; copper nail and washer 1,785.50
- Murphy, 4.0 mi. E. thence 4.45 mi. N. from, 1.70 mi. SE. of Tomatla gaging station, 65 ft. SE. of T-rd. S., in NW. corner of yard at white house, in root on W. side of 30-in. maple tree; copper nail and washer, painted "U.S.B.M. 1677.1" 1,677.03
- Tomatla gaging sta., 1.0 mile SE. of, 60 ft. E. of private rd. fork and 4 ft. above rd. fork elevation, 28 ft. NE. of rd., in root on W. side of 20-in. oak tree; copper nail and washer, painted "U.S.B.M. 1615.7" 1,615.64
- Murphy, 5.5 mi. NE. of, 0.4 mi. SE. of Tomatla gaging station, 250 ft. E. of E. edge of ford at Rogers Creek, 13 ft. N. of rd. at curve, in root on S. side of 30-in. maple tree; copper nail and washer, painted "U.S.B.M. 1576.3" 1,576.28

ORDER THIRD

Adj. 1929 GENERAL ADJUSTMENT

BK. B7003

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTIES

-7-

NGVD 29  
Elevations

Murphy, 4.93 mi. NE. of by rail, thence 0.12 mi. E. of by rd., 400 ft. E. of rd. fork on U.S. Highway 19, 6 ft. S. of rd., 6 ft. W. of SW. corner of bridge over Valley River, 16 ft. NW. of selsaes, on top of concrete step at rd. elevation, U.S.G.S. gaging station reference tablet, not stamped, painted "U.S.P.B.M. 1574.7" 1,574.612

Reference mark, 73 ft. NW. of tablet, 42 ft. N. of rd., on rock outcrop; chiseled square 1,569.09

Murphy, 4.6 mi. E. of by rail, 913 yards E. of milepost No. 118, 675 ft. W. of R. R. water tank, 30 ft. S. of S. rail, 6 inches below base of rail, 8 inches above grade across county rd. from R. R. in top of concrete post; standard C.&G.S. disk stamped "A 54 1933 1599.339" 1,600.341

Murphy, 4.6 mi. NE. of, about 300 ft. W. of Tomatla School, 9 ft. SW. of C.&G.S. post stamped "A 54 1933", 15 ft. SE. of rd., top of concrete post; plain bronze tablet marked "N+C and stamped "301", painted "U.S.P.B.M." 1,600.460

BOOK B.7004

FROM JUNCTION OF HIGHWAY 64 AND MISSION RD. ALONG RDS. E. TO MISSION THENCE N. TO A POINT. 3.1 MI. S. OF MARBLE.

Murphy, 6.15 mi. E. of, at top of ridge, 30 ft. NW. of private rd. forks, on bank 3 ft. above rd. level, in root on W. side of 12-in. maple tree; copper nail and washer, painted "U.S.B.M. 1792.0" 1,791.86

Reference mark, 110 ft. NW. of tablet 120 ft. E of private rd. fork, 20 ft. N. of rd. at center of plank bridge over Mission Branch, on rock outcrop, at rd. level; chiseled square, painted "R.M." (Note: U.S.E.D. 25" not found) 1,622.82

Murphy, 6.8 mi. E. of, 210 ft. E. of private rd. fork, 100 ft. SE. of Mission Branch plank bridge, 50 ft. S. of highway, 12 ft. N. of private rd., on large rock outcrop; standard tablet stamped "G W M 93 1936 1627" painted "U.S.P.B.M. 1627.0" 1,626.914

Murphy, 7.6 mi. E. of, 1.0 mi. W. of Andrews Dam by rd., 0.6 mi. below Andrews Dam, at mileage 105.5, 15 ft. NW. of rd., 5 ft. W. of W. H Sudderth's mail box, 4 ft. N. of large post oak tree; iron pipe with galvanized cap with marking Aug. 1923 47" (not legible as pipe has been pounded down flush with ground, "U.S.E.D. 24 1620.662" 1,621.688

NOTE: Mail box moved across rd. He says name is spelled Sudderth not Sudderth as on topographic map.

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA BY G.W. MOORE, 1936 ALTITUDE ABOVE  
 MEAN SEA LEVEL  
 ORDER THIRD ADJ. 1929 GENERAL ADJUSTMENT (Feet)  
 BK. B7004  
 RECOPY 12/8/55 lmk CLAY, CHEROKEE AND GRAHAM COUNTIES

-8-

- Murphy, 8.05 mi. E. of, 0.55 mi. NW. of Andrews Dam, 132 ft. E. of wood bridge over Clouthorn Branch, 160 ft. W. of rd. fork at Mission, 14 ft. N. of rd., in fence line, in root on N. side of 15-in. oak tree; copper nail and washer, painted "U.S.B.M. 1618.0" 1,617.877
- Murphy, 8.1 mi. E. to Mission thence 0.75 mi. N. from, 700 ft. S. of rd. fork NE., 20 ft. E. of Mission Rd., 65 ft. S. of fence corner, on 3.5 ft. bank at top of hill, in root on W. side of 15-in. maple tree; copper nail and washer, painted "U.S.B.M. 1716.0" 1,715.88
- Reference mark, 200 ft. SW. of tablet, 120 ft. SW. of Tennessee and North Carolina R. R. crossing, 27 ft. S. of rd., in root on N. side of 30-in. lone oak tree; copper nail and washer 1,725.74
- Murphy, 8.1 mi. E. of Mission, thence 1.25 mi. N. from, 78 ft. NE. of T. & N.C. R. R. crossing, 6.1 ft. above R. R. crossing, 14 ft. NW. of private rd. fork SE., top of large boulder; standard tablet stamped "G W M 94 1936 1719" 1,718.680
- Mail box post 12 ft. NE. painted "U.S.P.B.M. 1718.0"
- Murphy, 8.1 mi. E. to Mission, thence 2.1 mi. W. from, about 1.6 mi. E. of Peachtree, 65 ft. E. of T-rd. S., 11 ft. N. of rd., 8 ft. W. of fence corner, in root on SW. side of 25-in. hickory tree; copper nail and washer, painted "U.S.B.M. 1761.3" 1,761.28
- Reference mark, 30 ft. S. of tablet, 14 ft. E. of rd., on rock outcrop; chiseled square 1,854.75
- Murphy, 8.1 mi. E. to Mission, thence 3.0 mi. N. from 0.24 mi. S. of Upper Peachtree church, on point of hill midway between two wooden bridges over Peachtree Creek, 16 ft. E. of rd., on rock outcrop; standard tablet stamped "G.W.M. 95 1936 1857", painted "U.S.P.B.M. 1857" 1,857.325
- Murphy, 8.1 mi. E. to Mission, thence 3.83 mi. N. from, 0.6 mi. N. of Upper Peachtree Church, 110 ft. S. of top of hill, 7 ft. W. of rd., in root on SE. side of 10-in. persimmon tree; copper nail and washer, painted "U.S.B.M. 1959.3" 1,959.26
- Murphy, 8.1 mi. E. to Mission, thence 4.37 mi. N. from, 1.13 mi. N. of Upper Peachtree church, in saddle, 16 ft. N. of rd. fork NE., in root on W. side of 12-in. oak tree; copper nail and washer, painted "U.S.B.M. 2067.6" 2,067.54
- Murphy, 8.1 mi. E. of Mission, thence 4.9 mi. N. from, 1.65 mi. N. of Little Peachtree Church, 105 ft. N. of saddle at Indian grave gap, 8.2 ft. lower than highest elevation in gap, 7 ft. E. and 2.2 ft. above rd., on rock outcrop; standard tablet stamped "G W M 96 1936 2141.1" painted "U.S.P.B.M. 2141.3" 2,141.213



ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK. B7004

RECOPY 12/9/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTIES

NGVD 29  
Elevations

-9-

- Reference mark, 135 ft. S. of tablet, 32 ft. SE. of top of saddle in Indian Grave gap, on 3-ft. bank, 7 ft. E. of rd., in root on SW. side of 10-in. oak tree; copper nail and washer 2,150.80
- Murphy, 8.1 mi. SE. to Mission thence 5.53 mi. W. of Marble, 3.9 mi. S. of, at foot of grade, 0.65 mi. N. of Indian grave gap, 140 ft. east of creek, 225 ft. W. of barn, 25 ft. S. of rd. and 5.2 ft. above rd., in fence line of pasture, in root on NE. side of 35-in. oak tree; copper nail and washer, painted "U.S.B.M. 1858.3" 1,858.26
- FROM A POINT 1.7 MI. SE. OF TOMATLA, NE. AND N. ALONG RD. TO MARBLE
- Murphy, 4 mi. E. thence 5.15 mi. NE. from, 5.35 mi. S. thence 0.83 mi. SW. from Marble, 59 ft. E. of drain, 10 ft. N. of rd., in root on W. side of 20-in. apple tree; copper nail and washer, painted "U.S.B.M. 1707.3" 1,707.22
- Marble, 4.5 mi. S. of along Marble-Peachtree rd., 80 ft. N. of T-rd. SW., 15 ft. W. of rd., on E. side of 8-in. poplar tree; R. R. spike, painted white, painted "U.S.B.M. 1754.1" 1,754.00
- Marble, 4.0 mi. S. of along Marble-Peachtree rd., 21 ft. SE. of rd., 10 ft. NW. of T. & N.C. R. R., 85 ft. NE. of drain, top of marble post; standard tablet stamped "GWM 97 1936 1808", painted "U.S.P.B.M. 1807.6" 1,807.477
- Reference mark, 140 ft. NE. of tablet, 20 ft. SE. of T. & N.C. R. R., in right-of-way fence, in base on W. side of 6-in. poplar tree; R. R. spike, painted white 1,807.30
- Marble, 3.2 mi. S. of, 42 ft. E. of India grave gap rd., 90 ft. NW. of R. R. crossing, 38 ft. W. of R. R., in root on SE. side of 8-in. twin persimmon tree; copper nail and washer, painted "U.S.B.M. 1,777.2" 1,777.18
- Marble, 2.65 mi. S. of, 235 ft. S. of rd. fork E., 100 ft. SE. of wood bridge over Derriberry Branch, 80 ft. E. of Marble-Peachtree rd., in root on NE. side of 15-in. apple tree; copper nail and washer, painted "U.S.B.M. 1706.7" 1,706.66
- Reference mark, 36 ft. W. of tablet, 9 ft. N. of rd., 8 ft. SW. of fence corner, top of boulder; chiseled square 1,670.62
- Marble, 1.9 mi. S. of, 125 ft. E. of T-rd. E. from Marble-Peachtree rd., 10 ft. N. of Vengeance Creek rd., on rock outcrop; standard tablet stamped "G W M 98 1936 1672," painted "U.S.P.B.M. 1672.3" 1,672.236
- Marble, 1.0 mi. S. of, at steel highway bridge over Valley River, 150 ft. N. of T-rd. N. to Marble, on W. wing wall of S. masonry abutment; chiseled square, painted "U.S.B.M. 1628.7" 1,628.62

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By G.W. MOORE, 1936 ALTITUDE ABOVE  
MEAN SEA LEVEL

ORDER THIRD Adj. 1929 GENERAL ADJUSTMENT  
BK.B7004  
RECOPY 12/9/55 lmk CLAY, CHEROKEE AND GRAHAM COUNTIES

(Feet)

-10-

Marble sta., 0.6 mi. S. of, at top of hill in yard, 15 ft. SE. of  
rd., in root on E. side of 25-in. oak tree; copper nail and washer,  
painted "U.S.B.M. 1712.4" 1,712.33

Murphy, 9.1 mi. E. by rail, 755 ft. W. of Marble depot, 65 ft. E. of  
milepost 113, 18 ft. S. of S. rail, 17 ft. N. of center of N.C.  
Highway 10, 1 ft. above top of rail, 8 inches above grade, in top of  
C&GS post; standard disk stamped "C 54 1933" 1,685.607

Andrews, 5.9 mi. W. by rail, 760 ft. E. of milepost 113, 60 ft. W. of  
Marble depot, 33 ft. N. of center of N.C. Highway 10, 15 ft. S. of  
S. rail, 2 ft. above top of rail, 8 inches above grade, in top of concrete  
post; standard disk stamped "D 54 1933" C&GS 1,686.578

BK.B6908

BY R.P. WILLINGHAM, 1936

FROM WAYAH BALD QUADRANGLE NW. ALONG RD. TO ANDREWS

Andrews, 5.3 mi. E. of, on Franklin Road, 4.1 mi. E. of Junaluska Terrace,  
20 ft. N. of center line of rd., in root on S. side of 30-in. oak tree;  
copper nail and washer, painted "U.S. 2548.5 B.M." 2,550.40

Andrews, 4.2 mi. E. of, 20 ft. E. of center line of bridge over Junaluska  
Creek, about 225 ft. NW. of underpass, in root on N. side of 24-in.  
hemlock tree; copper nail and washer, painted "U.S. 2223.5 B.M." 2,225.35

✓ Andrews, 3.2 mi. E. of, 80 ft. N. of N. end of wooden bridge over Junaluska  
Creek, 40 ft. NW. of center line of rd. at curve, at foot of ridge,  
in concrete post; standard tablet stamped "K 13 1934", painted  
"U.S. 2043.6 P.B.M." 2,045.371

Reference mark, No. 1, 150 ft. SE. of tablet, on E. side of R. R., in  
edge of creek, in root on N. side of 20-in. oak tree; copper nail and  
washer 2,042.07

Reference mark 2, 150 ft. S. of tablet, on W. side of rd., in root on  
NW. side of 12-in. spruce tree; copper nail and washer 2,038.33

Andrews, 1.7 mi. E. of, 175 ft. SE. of rd. fork, at W. edge of yard in  
front of old residence, 20 ft. NE. of center line of rd., in root on E.  
side of 36-in. oak tree; copper nail and washer, painted "U.S. 1881.8  
B.M." 1,883.563

Andrews, 1.3 mi. E. of, 40 ft. NE. of crossrds., 40 ft. NE. of center line  
of highway 19, about 700 ft. N. of Junaluska Terrace Hotel, in root  
on SE. side of 14-in. oak tree; copper nail and washer, painted  
"U.S. 1839.5 B.M." 1,841.35

ORDER THIRD

Adj. 1929 GENERAL ADJUSTMENT

(Feet)

BK. 6908

NGVD 29  
Elevations

RECOPY 12/9/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTIES

-11-

Andrews, 0.7 mi. E. of, on SE. wing wall abutment of concrete highway bridge; chiseled square

1,799.77

Andrews, 25 ft. S. of Southern Ry. Sta., in N. edge of park, in concrete post; standard disk stamped "G 54 1933" (U.S.C. & G. S.)

1,772.995

## FROM WAYAH BALD QUADRANGLE NW. ALONG HIGHWAY 64 TO HAYESVILLE

Hayesville, 5.3 mi. E. of, 140 ft. N. of NW. corner of Elf brick school-house, 40 ft. S. of center line of highway 64, 20 ft. above highway level, in root on N. side of 20-in oak tree; copper nail and washer, painted "U.S. 1962.7 B.M."

1,963.94

Hayesville, 4.9 mi. E. of, 0.5 mi. W. of Elf school, 25 ft. S. of center line of Highway 64, about 200 ft. NW. of white dwelling, in root on N. side of 14-in. oak tree; copper nail and washer, painted "U.S. 1891.0 B.M."

1,892.24

Hayesville, 3.7 mi. E. of, 50 ft. W. of crossroads, 50 ft. NE. of chicken house, 25 ft. S. of center line of Highway 64, in root on NE. side of 8-in. oak tree; copper nail and washer, painted "U.S. 1925.7 B.M."

1,926.92

Hayesville, 2.8 mi. E. of, 12 ft. NE. of center line of Highway 64, on N. concrete wing wall abutment of highway bridge over Hiawasse River; chiseled square, painted "U.S. 1821.3 B.M."

1,822.59

Hayesville, 1.9 mi. E. of, 150 ft. E. of junction of Highway 64 and 287, 15 ft. S. of center line of Highway 64, on E. end of S. head wall of concrete bridge; standard tablet stamped "R.P.W. 4 1934"

1,803.687

Reference mark, 30 ft. S. and 12 ft. W. of tablet, on E. end of N. head wall of small concrete bridge; chiseled square

1,803.24

Hayesville, 0.9 mi. E. of, 60 ft. S. of crest of ridge, 40 ft. E. of center line of Highway 64, in root on SE. side of 30-in. oak tree; copper nail and washer

1,876.56

Hayesville, 110 ft. S. of entrance to courthouse, 20 ft. E. of sidewalk; top of monument lettered "N C G S - U S G S 1900 No 9"

1,890.731

## FROM HAYESVILLE NE. ALONG RD. INTO WAYAH BALD QUADRANGLE.

Hayesville, 0.7 mi. N. of, on N. guard rail at center of concrete bridge over Hiawasse River; chiseled square, painted "1799.78 (U.S.E.D. 10)

1,800.381

Hayesville, 0.7 mi. N. of, on NE. wing wall abutment of concrete highway bridge over Hiawasse River; chiseled square, painted "U.S. 1797.6 B.M."

1,798.79

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By R.F. WILLENHAM, ALTITUDE ABOVE  
1936 MEAN SEA LEVEL  
(Feet)

ORDER THIRD ADJ. 1929 GENERAL ADJUSTMENT

BK. B6908

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTIES

-12-

Hayesville, 1.1 mi. N. of, 45 ft. NW. of intersection of T-rd. W., 35 ft. W. of center line of rd., in root on E. side of 8-in. oak tree; copper nail and washer, painted "U.S. 1838.6 B.M." 1,839.83

Hayesville, 1.9 mi. N. of, 75 ft. S. of center line of rd., 20 ft. W. of picket fence, in root on N. side of 12-in. black gum tree; copper nail and washer, painted "U.S. 1859.8 B.M." 1,860.99

✓ Hayesville, 2.8 mi. NE. of, 45 ft. N. of intersection of T-rd. S., 30 ft. N. of center line of main rd., in concrete post; standard tablet stamped "K 31 1934" painted "U.S. 1923.7 F.B.M." 1,924.698

Reference mark, 70 ft. W. of tablet, in root on S. side of 24-in. oak tree; copper nail and washer, painted "U.S. 1915.3 R.B.M." 1,916.50

Hayesville, 3.4 mi. NE. of, 100 ft. NE. of intersection of T-rd. E., 40 ft. E. of bridge over Tusquittee Creek, 25 ft. N. of center line of T-rd., in root on S. side of 24-in. oak tree, 2.5 ft. from base; copper nail and washer, painted "U.S. 1852.1 B.M." 1,852.1

Hayesville, 4.2 mi. NE. of, 20 ft. NE. of stream crossing, 12 ft. NE. of rd. N.W., on top of lowest rock in outcrop; chiseled square 1,837.81

Hayesville, 5.1 mi. NE. of, 20 ft. E. and 20 ft. S. of front entrance to Tusquittee Baptist Church, 50 ft. NW. of rd., in root on N. side of 12-in. oak tree; copper nail and washer 2,004.87

Hayesville, 5.7 mi. NE. of, 200 ft. N. of Phillips Store, 90 ft. NE. of intersection of center line of Y-rds., 10 ft. N. of center line of rd., in root on N. side of 12-in. sourwood tree; copper nail and washer 1,961.08

BK. B7004

BY. C.W. MOORE, 1936

FROM BLAIRSVILLE QUADRANGLE NE. ALONG HIGHWAY TO HAYESVILLE

✓ Hayesville, 4.5 mi. SW. of, 36 ft. E. of Webb Creek rd., fork N., on E. end of S. head wall of large concrete culvert over Webb Creek; standard tablet stamped "G.W.M. 100 1936 1786", painted "U.S.P.B.M. 1785.5" 1,785.335

Reference mark, 26 ft. NW. of tablet, on W. end of N. head wall of large concrete culvert over Webb's Creek; chiseled square 1,785.39

Hayesville, 3.85 mi. SW. of, 210 ft. E. of SE. corner of Shady Grove church across rd. from farmhouse, on NE. end of NW. heading of masonry culvert; chiseled square, painted "U.S.B.M. 1846.1" 1,845.94

ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

NGVD 29  
Elevations

BK. B7004

RECOPY 12/9/55 Lmk

CLAY, CHEROKEE AND GRAHAM COUNTIES

-13-

- Hayesville, 3.17 mi. SW. of, 20 ft. SW. of Matthewson Cove Rd. forks,  
17 ft. NW of U.S. Highway 64, in root on S. side of 48-in. oak tree;  
copper nail and washer, painted "U.S.B.M. 1974.5" 1,974.33
- Hayesville, 2.5 mi. SW. of, at top of hill, 33 ft. SW. of mail boxes,  
on SW. end of NW. heading of masonry culvert; chiseled square,  
painted "U.S.B.M. 1968.5" 1,968.28
- Hayesville, 1.75 mi. SW. of, on U.S. Highway 64, crossing over fork of  
Black Creek, on S. end of W. head wall of large concrete culvert;  
standard tablet stamped "G W M 101 1936 1865," painted "U.S.P.B.M.  
1865.1" 1,864.955
- Reference mark, 26 ft. NE. of tablet, on N. end of E. head wall of large  
concrete culvert over Black Creek; chiseled square 1,864.78
- Hayesville, 1.26 mi. SW. of, top of hill at rd. fork W., center of  
pavement on U. S. Highway 64, painted "1,942.107" 1,941.91
- Hayesville, 0.94 mi. SW. of, on long grade, .032 mi. NE. of T-rd. W.,  
at top of hill, on NE. end of SE. heading of masonry culvert; chiseled  
square, painted "U.S.B.M. 1893.7" 1,893.54
- Hayesville, at mileage 116.6, 150 ft. S. of Clay County courthouse, 10 ft.  
E. of sidewalk, center of stone on meridian line; monument chiseled  
"N.C.G.S. U. S. G. S. 1900" (U.S.E.D. 9) no tablet 1,890.731
- Haesville, 75 ft. N.W. of NW. side of Clay County courthouse, 55 ft. S. of  
cross streets at N. corner of square, 18 ft. SW. of N. corner of masonry  
wall around courthouse grounds, center of stone on meridian line;  
monument chiseled "N.C.G.S." "U.S.G.S. 1900," (no tablet) not painted 1,890.096
- Hayesville, 0.65 mi. N. of, on Tusquitee Road, 150 ft. NE. of rd., forks,  
at concrete highway bridge over Hiwassee River, top of W. wing wall of  
SW. abutment; standard tablet stamped "G.W. M 102 1936 1799", painted  
"U.S.P.B.M. 1799.1" DEST 86 1,798.901
- FROM A POINT 3.45 MI. NE. OF HAYESVILLE W. ALONG RD. TO SHALLOW FORD BRIDGE
- Hayesville, 3.62 mi. NE. of ground at T-rd. W. elev. 1873.970" 1,873.9
- Hayesville, 3.6 mi. NE. of thence 0.7 mi. W. from, 5 ft. N. of rd., 3 ft.  
above rd., 6 ft. S. of trunk of 22-in. oak tree, in root; copper nail  
and washer, painted "U.S.B.M. 1839.0" 1,838.95
- Hayesville, 3.6 mi. N.E. thence 1.5 mi. W. from, 7.55 mi. E. of Shallow  
Ford bridge, 45 ft. NW. of wood bridge over creek, 35 ft. N. of rd.  
forks, on rock outcrop; standard tablet stamped "G W M 103 1936 1870,"  
painted "U.S.P.B.M. 1869.9" 1,869.809

QUAD. BIG STAMP KNOB      STATE NORTH CAROLINA      By C.W. MOORE, 1936      ALTITUDE ABOV.  
 ORDER THIRD      ADJ. 1929 GENERAL ADJUSTMENT      MEAN SEA LEVEL  
 BK.B7004

RECOPY 12/9/55 Lmk      CLAY, CHEROKEE AND GRAHAM COUNTIES

-14-

Reference mark, 69 ft. S. of tablet, 10 ft. W. of rd., on rock outcrop; chiseled square	1,866.98
Shallow Ford bridge, 6.85 mi. E. of, 58 ft. SW. of rd. fork E., 4 ft. S. of fence, 6.8 ft. below rd. fork elevation, in root on S. side of 12-in. oak tree; copper nail and washer, painted "U.S.B.M. 1840.7"	1,840.69
Shallow Ford bridge, 6.05 mi. E. of, 45 ft. N. of ford, 60 ft. E. of rd. fork N., at W. edge of Carver Creek, top of large flat boulder; chiseled square, painted "U.S.B.M. 1840.0"	1,839.96
Shallow Ford bridge, 5.9 mi. E. of, 30 ft. NW. of rd. fork N. to Andrews, 12 ft. W. of second class rd. N., on bank 3.6 ft. above top of hill on main rd., in root on W. side of 12-in. oak tree; copper nail and washer, painted "U.S.B.M. 1888.0"	1,887.93
Shallow Ford bridge, 5.5 mi. E. of, 135 ft. W. of R. R., 155 ft. W. of rd., 22 ft. W. of concrete gaging well, on concrete retaining wall at edge of Hiwassee River; U.S.G.S. gaging station reference tablet (not stamped), painted "U.S.B.M. 1764.0"	1,764.59
Shallow Ford bridge, 5.5 mi. E. of, 115 ft. W. of R. R., 7.7 ft. S. of concrete gaging well, 20 ft. E. of Hiwassee River, top of concrete post; U.S.G.S. gaging station reference tablet (not stamped) painted "U.S.B.M. 1769.9"	1,769.851
Shallow Ford bridge, 4.8 mi. E. of, on top of ridge, 82 ft. W. of church, 15 ft. N. of rd., in root on SE. side of 25-in. oak tree; copper nail and washer, painted "U.S.B.M. 1886.2"	1,886.20
Shallow Ford bridge, 4.3 mi. E. of, 100 ft. SE. of R. R. culvert, 16 ft. NE. of R. R., 7 ft. NE. of rd., top of rock outcrop, at rd. level; chiseled square, painted "U.S.B.M. 1758.6"	1,758.58
Reference mark, 88 ft. NE. of tablet, 9 ft. NW. of R. R. tracks, on rock outcrop; chiseled square	1,753.95
Shallow Ford bridge, 3.9 mi. E. of 95 ft. SW. of rd. at drain crossing, 10 ft. NE. of R. R. tracks, on W. side of drain, top of boulder; standard tablet stamped "G W M 104 1936 1751", painted "U.S.P.B.M. 1750.7"	1,750.701
Shallow Ford bridge, 2.95 mi. E. of, at wooden highway bridge over Fires Creek, 700 ft. SE. of rd. forks, on S. wing wall of R. masonry abutment; chiseled square 11 ft. above creek, painted "U.S.B.M. 1769.7"	1,769.7
Shallow Ford bridge, 2.82 mi. E. of, ground at rd. forks 700 ft. NW. of Fires Creek bridge	1,794.7

92

QUAD. BIG STAMP KNOB

STATE NORTH CAROLINA

By C. W. MOORE, 1936

ALTITUDE ABOVE  
MEAN SEA LEVEL  
(Feet)

ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK. B7004

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRANAM COUNTIES

NGVD 29  
Elevations

-15-

- Shallow Ford bridge, 2.5 mi. E. of, at top of hill, 20 ft. S. of T-rd. W. to school, in root on W. side of 10-in. oak tree; copper nail and washer, painted "U.S.B.M. 1883.5" 1,883.45
- Shallow Ford bridge, 1.9 mi. E. of, 30 ft. W. of rd. fork and ford over Watson Branch, about 400 ft. NE. of U.S.E.D. on R. R. culvert, 10 ft. N. of rd., on rock outcrop; standard tablet stamped "G W M 105 1936 1722," painted "U.S.P.B.M. 1722.3" 1,722.228
- Reference mark, 78 ft. SW. of tablet, 18 ft. NW. of rd., on rock outcrop; chiseled square 1,726.41
- Andrews Dam, 4 mi. above, at mileage 110.1, 60 ft. E. of rd., in top of culvert over small branch, at mouth of Long Branch (Watson Branch), in round stone at E. end of N. head wall of stone culvert; chiseled square, painted "U.S.B.M. 1712.2" (U.S.E.D. -20) 1,712.058
- Shallow Ford bridge, 1.0 mi. E. of, about 200 ft. SW. of rd., 50 ft. W. of R. R. culvert, over Curtis Branch, 20 ft. N. of R. R. tracks, top of large boulder; chiseled square, painted "U.S.B.M. 1701.2" 1,701.17
- FROM MARBLE N. ALONG RD. TO LITTLE SNOWBIRD CREEK THENCE SW. ALONG TRAIL AND RD. BY WAY OF LUCY GAP INTO MURPHY QUAD ANGLE.
- Andrews, 5.9 mi. W. by rail, 760 ft. E. of milepost 110, 60 ft. W. of Marble depot, 33 ft. N. of center of N.C. Highway 10, 15 ft. S. of S. rail and 2 ft. above top of rail, 8 inches above grade, top of concrete post; standard tablet stamped "D 54 1933", C&CS 1,686.578
- Marble, 0.8 mi. N. of, 290 ft. S. of rd. fork E., 80 ft. SW. of W. end of foot bridge over Hyatt Creek, 9 ft. W. of rd., top of boulder; chiseled square, painted "U.S.B.M. 1724.7" 1,724.64
- Marble, 0.9 mi. N. of, rd. fork at ford over Hyatt Creek 1,734.2
- Marble, 1.54 mi. N. of, at top of first ridge, 15 ft. W. of rd., 3 ft. W. of fence, in NW. root of 10-in. lone oak tree; copper nail and washer, painted "U.S.B.M. 200.9" 2,000.80
- Reference mark, 35 ft. SE. of tablet, 10 ft. NW. of rd. fork, on flat rock outcrop, ground level; chiseled square 2,095.96
- Marble, 2.1 mi. N. of, 45 ft. NW. of secondary rd. fork N., 80 ft. NW. of pole bridge over creek, 18 ft. NE. of main rd., on rock outcrop; standard tablet stamped "G W M 106 1936 2103", painted "U.S.P.B.M. 2103.5" 2,103.413
- BK.B. 7004, B7005
- Marble, 2.75 mi. N. of, 30 ft. E. of rd. at ford, on N. side of Almond Creek, on rock outcrop; chiseled square, painted "U.S.B.M. 2362.4" 2,362.41

QUAD. BIG STAMP KNOB      STATE NORTH CAROLINA      BY C.W. MOORE, 1936      ALTITUDE ABOVE  
 MEAN SEA LEVEL )  
 ORDER THIRD      ADJ. 1929 GENERAL ADJUSTMENT      (Feet)  
 BK.B7004, B7005  
 RECOPY 12/8/55 lmk      CLAY, CHEROKEE AND GRAMM COUNTIES

-16-

Marble, 3.4 mi. N. of, 8 ft. N. of rd., S. side of 25-in. gum tree;  
 R.R. spike, painted white, tree painted "U.S.B.M. 2761.7"      2,761.65

Marble, 3.7 mi. N. of, at sharp bend in rd., 7 ft. E. of rd., top of  
 boulder; chiseled square, painted "U.S.B.M. 3009.1"      3,009.09

Marble, 4.25 mi. N. of, 27 ft. SW. of rd. fork, at top of Porterfield  
 Gap, 2.6 ft. above rd. at gap, top of boulder; standard tablet stamped  
 "G.W.M. 107 1936 3462," painted "U.S.P.B.M. 3461.8"      3,461.769

Reference mark, 55 ft. N. of tablet, in wye of rd. forks N., in root on  
 NE. side of 25-in. gum tree; copper nail and washer      3,456.57

Marble, 4.7 mi. N. of, 0.45 mi. N. of Porterfield Gap, 50 ft. N. of  
 wood bridge over drain, 5.5 ft. above bridge level, 8 ft. W. of rd.,  
 top of boulder; chiseled square, painted "U.S.B.M. 3281.6"      3,281.56

Marble, 5.3 mi. N. of, on S. side of Little Snowbird Creek, at Long  
 Bottoms, about 500 ft. S. of house, 115 ft. E. of E. side of ford over  
 Little Snowbird Creek, 85 ft. W. of trail fork at foot of grade from  
 Porterfield Gap, 290 ft. E. of rd. forks, top of boulder; standard  
 tablet stamped "G W M 108 1936 2980," painted "U.S.P.B.M. 2979.7"      2,979.764

Reference mark, 116 ft. NE. of tablet, 30 ft. NE. of rd. fork, in base on  
 S. side of 35-in. oak tree; R. R. spike, painted white      2,978.20-

BK.B7005

At Long Bottoms, water elevation of ford over Little Snowbird Creek      2,978.1

Long Bottoms, 0.2 mi. W. of, water elevation of ford over Little Snow-  
 bird Creek      2,998.3

Marble, 5.3 mi. N. to Long Bottoms, thence 0.75 mi. from, about 200 ft. N.  
 of house, 40 ft. S. of S. edge of ford over Little Snowbird Creek, at  
 end of car rd., 6 ft. W. of rd., top of boulder; chiseled square,  
 painted "U.S.B.M. 3060.8"      3,060.84

Long Bottoms, 0.8 mi. W. of, water elevation at ford over Little Snow-  
 bird Creek      3,065.66

Marble, 5.3 mi. N. to Long Bottoms, thence 1.2 mi. W. along Little  
 Snowbird Creek trail, about 180 ft. W. of trail fork to W., 10 ft. SW.  
 of logging rd. N., on N. bank of creek, 2.6 ft. above water, in root on  
 N. side of 12-in. maple tree; copper nail and washer, tree painted  
 "U.S.B.M. 3102.8"      3,102.8

Long Bottoms, 1.28 mi. W. of, ford over Little Snowbird Creek      3,103.1



ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK. B7005

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTIES

-17-

NGVD 29  
Elevations

- Marble, 5.3 mi. N. to Long Bottoms, thence 1.8 mi. W. along Little Snowbird Creek trail, in meadow, 240 ft. NE. of steam boiler at abandoned sawmill, 60 ft. N. of trail at ford, 9 ft. above water level at ford, top of boulder; chiseled square, boulder painted "U.S.B.M. 3135.2" 3,135.31
- ✓ Marble, 5.3 mi. N. to Long Bottoms, thence 2.3 mi. W. of, 1.5 mi. E. of Lucy Gap, about 70 ft. SE. of house, at W. edge of ford through Little Snowbird Creek, 10 ft. N. of rd., top of boulder; standard tablet stamped "G W M 109 1936 3152," fence painted "U.S.P.B.M. 3152.0" 3,152.151
- Reference mark, 66 ft. W. of tablet, 55 ft. S. of front door of house, 5 ft. S. of rd. top of boulder; chiseled square, water elevation at ford 3,151.689 3,154.74
- ~~Marble, 5.3 mi. N. to Long Bottoms, thence 3.2 mi. W. of, 0.6 mi. E. of Lucy Gap, 60 ft. SW. of SW. corner of house, 40 ft. N. of trail and 5 ft. below trail, about 210 ft. W. of ford on Little Snowbird Creek, in root on E. side of 8-in. apple tree; copper nail and washer, painted "U.S.B.M. 3230.1" 3,230.26~~
- Marble, 5.3 mi. N. to Long Bottoms, thence 3.7 mi. E. from, 6.85 mi. NE. of Grandview post office, 0.1 mi. NE. of Lucy Gap, 8 ft. SE. of trail, 4.75 ft. above trail, on prominent rock outcrop; standard tablet stamped "G W M 110 1936 3400," painted "U.S.P.B.M. 3400.5" 3,400.616
- Reference mark, 46 ft. SW. of tablet, 7 ft. NW. of trail, in rock outcrop; chiseled square 3,402.69
- Grandview post office, 6.75 mi. NE. of, 17 ft. SE. of highest point on trail through Lucy Gap, 1 ft. above gap elevation, 24 ft. S. of open gate, in root on N. side of 9-in. walnut tree; copper nail and washer, painted "U.S.B.M. 3466.8" 3,466.98
- Grandview Post office, 6.45 mi. NE. of, 0.3 mi. SW. of Lucy Gap, on grade, 10 ft. W. of trail, in root on N. side of 36-in. hickory tree; copper nail and washer, painted "U.S.B.M. 3068.4" 3,068.57
- Grandview post office, 6.1 mi. NE. of, 0.64 mi. SW. down grade from Lucy Gap, 60 ft. W. of last house on rd. to Lucy Gap, 16 ft. W. of trail, 100 ft. NE. of end of rd., at group of large boulder, top of boulder; chiseled square, painted "U.S.B.M. 2585.4" 2,585.53
- Grandview post office, 5.7 mi. NE. of, 1.05 mi. SW. of Lucy Gap, 40 ft. N. of Hanging Dog Creek, 20 ft. SE. of T-rd. NE. to Lucy Gap, 10 ft. N. of Hanging Dog Creek rd., 4.5 ft. above rd. forks, top of boulder; chiseled square, painted "U.S.B.M. 2343.2" 2,343.31

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By C.W. MOORE, 1936 ALTITUDE ABOVE  
 MEAN SEA LEVEL )  
 ORDER ~~RECORDED~~ ADJ. 1929 GENERAL ADJUSTMENT (Feet)  
 BK. B7005  
 RECOPY 12/8/55 lmk CLAY, CHEROKEE AND GRAHAM COUNTIES

-18-

- Grandview post office, 4.9 mi. NE. of, 1.85 mi. SW. of Lucy Gap, 75 ft. E. of mill, 25 ft. N. of rd. at trail fork, in root on S. side of 14-in. persimmon tree; copper nail and washer, painted "U.S.B.M. 2133.5" 2,133.66
- FROM A POINT 1.9 MI. S. OF MARBLE E. ALONG RD. AND TRAIL TO A POINT 2.4 MI. S. OF ANDREWS
- Marble, 1.9 mi. S. thence 0.9 mi. E. from, 65 ft. N. of wood bridge over Vengeance Creek, 20 ft. W. of rd., in root on E. side of 6-in. twin gum tree; copper nail and washer, painted "U.S.B.M. 1774.0" 1,773.87
- Marble, 1.9 mi. S. thence 1.56 mi. E. from, foot of hill, center of wood bridge over Vengeance Creek painted "1,886.094" 1,886.02
- Marble, 1.9 mi. S. thence 1.74 mi. E. from, 480 ft. NW. of rd. forks, 11 ft. NE. of rd., on 5.3-ft. bank, in base on S. side of 7-in. oak tree; R.R. spike, painted white, painted "U.S.B.M. 1927.6" 1,927.54
- Marble, 1.9 mi. S., thence 1.83 mi. E. from, ground at rd. fork SE. 1,947.87
- Marble, 1.9 mi. S. thence 2.4 mi. E. from, 1.5 mi. W. of Hog Pen gap, 230 ft. SE. of Joe Ledford's house, 85 ft. NE. of gate to pasture, 55 ft. N. of rd., top of boulder; standard tablet stamped "G.W.M. 113 1936" 1949" painted "U.S.P.B.M. 1949.4" 1,949.270
- Reference mark, 68 ft. S. of tablet, 13 ft. S. of rd., 80 ft. W. of ford over Greybeard Creek, in fence, in root on W. side of 10-in. white locust tree; copper nail and washer 1,954.10
- Marble, 1.9 mi. S. thence 3.37 mi. E. from, 0.5 mi. W. of Hog Pen gap, 14 ft. S. of rd. where creek runs in rd., 14 ft. S. of Nancy Hawkins Branch, about 0.2 mi. W. of house at end of rd., in base on NW. side of 20-in. beech tree; copper nail and washer, painted "U.S.B.M. 2122.0" 2,121.90
- Marble, 1.9 mi. S. thence 3.74 mi. E. of, 0.12 mi. W. of Hog Pen gap, 70 ft. SE. of cross trails, in root on S. side of a multiple maple tree; copper nail and washer, painted "U.S.B.M. 2267.7" 2,267.65
- Marble, 1.9 mi. S. thence 3.86 mi. E. from, at Hog Pen gap, 43 ft. S. of highest pole on power line, 15 ft. S. of rd. at saddle, 3.2 ft. above rd., in root on N. side of 15-in. oak tree; copper nail and washer, painted "U.S.B.M. 2353.2" 2,353.10
- Marble, 1.9 mi. S. thence 4.36 mi. E. from, 0.5 mi. E. of power line crossing Hog Pen gap, 25 ft. N. of ford over Aaron Creek, 12 ft. W. of wagon rd., top of boulder; standard tablet stamped "G.W.M. 114 1936 2129", painted "U.S.P.B.M. 2129.0" 2,128.922

ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK. B7005

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRANHAM COUNTIES

-19-

NGVD 29  
Elevations

Reference mark, 47 ft. NE. of tablet, 25 ft. E. of wagon rd., in root on S. side of 30-in. oak tree; copper nail and washer	2,135.20
Marble, 1.9 mi. S. thence 5.12 mi. E. of, 2.5 S. thence 4.43 mi. W. from Andrews, 100 ft. SE. of small house, 85 ft. S. of ford over Alfred Creek, 8 ft. E. of rd. fork, on 2.5 ft. bank, in root on NE. side of 6-in. black walnut tree; copper nail and washer, painted "U.S.B.M. 1970.4"	1,970.36
Andrews, 2.5 mi. S. thence 3.68 mi. W. of, ford over Taylor Creek, painted "1881.978"	1,851.9
Andrews, 2.5 mi. S. thence 3.5 mi. W. from, 740 ft. SE. of Power line crossing rd., 60 ft. N. of rd., at U-bend at drain, 12 ft. W. of rd., on 5-ft. bank, in root on E. side of 24-in. oak tree; copper nail and washer, painted "U.S.B.M. 1953.6"	1,953.54
Andrews, 2.5 mi. S. thence 3.0 mi. W. from, 180 ft. NW. of house, 110 ft. SE. of gate, 12 ft. E. of rd., about 4.1 ft. above rd., on rock ledge; standard tablet stamped "G.W.M. 115 1936 1984," painted U.S.P.B.M. 1983.8"	1,983.762
Reference mark, 73 ft. W. of tablet, 73 ft. S. of gate, 40 ft. SW. of rd., in base on E. side of an inclined apple tree; copper nail and washer	1,972.77
Andrews, 2.5 mi. S. thence 2.6 mi. W. from, 170 ft. E. of Taylor Creek rd. fork, 14 ft. S. of rd., in base on W. side of 30-in. oak tree; R. R. spike, painted white, painted "U.S.B.M. 2079.1"	2,078.98
Andrews, 2.5 mi. S. thence 1.7 mi. W. from, 0.25 mi. SW. of tablet, "G.W.M. 116 1936," at sharp bend in rd. at foot of hill, 20 ft. N. of rd. forks, in root on S. side of 25-in. oak tree; copper nail and washer, painted "U.S.B.M. 2098.4"	2,098.35
Andrews, 2.5 mi. S. thence 1.45 mi. SW. of, 420 ft. NW. of Patham Creek plank bridge, 11 ft. E. of rd., 4.2 ft. above rd. on rock outcrop; standard tablet stamped "G.W.M. 116 1936 2064," painted "U.S.P.B.M. 2163.9"	2,063.802
Reference mark, 65 ft. NW. of tablet, 24 ft. W. of rd., in root on NE. side of 14-in. twin gum trees; copper nail and washer	2,058.18
Andrews, 2.5 mi. S. thence 0.6 mi. SW. from, 44 ft. NW. of rd. at drain, in root on NE. side of 30-in. maple tree; copper nail and washer, painted "U.S.B.M. 1956.0"	1,955.89

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By C.W. MOORE, 1936 ALTITUDE ABOVE  
MEAN SEA LEVEL )  
ORDER THIRD ADJ. 1929 GENERAL ADJUSTMENT (Feet)  
BK. B7005  
RECOPY 12/8/55 *lwk* CLAY, CHEROKEE AND GRAHAM COUNTIES  
-20-

FROM ANDREWS S. ALONG RD. AND TRAIL TO A POINT 5.9 MI. E. OF SHALLOW FORD BRIDGE.

- ✓ Andrews, 60 ft. S. of S. rail, 25 ft. W. of W. end of Andrews's depot, on level with top of rail, 10 inches above grade and at E. end of park between R. R. and street, in top of concrete post; standard tablet stamped "G 54 1933," C&GS 1,772.995
- Andrews sta., 0.5 mi. E. of, at top of hill, 35 ft. SE. of T-rd. N. to Robbinsville, on U. S. Highway 19, on S. heading of concrete culvert at rd. level; chiseled square, painted "U.S.B.M. 1809.5" 1,809.56
- Andrews, 0.77 mi. SE. of sta., on U. S. Highway 19, at concrete highway bridge over Colletts Creek, top of S. parapet wall of E. concrete abutment; chiseled square, painted "U.S.B.M. 1,798.0" 1,799.78
- Center line of bridge painted "1,798.2"  
NOTE: Map gives this as Tatham Creek but brass plate on bridge is Colletts Creek, repainted "U.S.B.M. 1799.7"
- Andrews, 1.54 mi. SE. of sta., 95 ft. NE. of top of hill, 25 ft. E. of rd., in root on W. side of 36-in. oak tree; copper nail and washer, painted "U.S.B.M. 1934.3" Center of rd. at top of hill 1936.1" 1,934.34
- Andrews, 1.97 mi. S. of, center of rd. at Rutter Lumber Co. R. R. crossing, 1,875.8-
- Andrews, 2.03 mi. S. of, 295 ft. SW. of Rutter Lumber Co. R. R. crossing, 46 ft. S. of wood bridge over McClellan Creek, 15 ft. NW of rd. at private rd. fork, in root on SE. side of 36-in. oak tree; copper nail and washer, painted "U.S.B.M. 1882.3" 1,882.40
- ✓ Andrews, 2.5 mi. S. of, 160 ft. S. of T-rd. N., 40 ft. W. of fence, in pasture, top of quartzite boulder; standard tablet stamped "G W M 117 1936" 1954" painted "U.S.P.B.M. 1954.4" 1,954.479
- Reference mark, 152 ft. SW. of tablet, 175 ft. SE. of rd., in root on S. side of 30-in. yellow pine tree; copper nail and washer 1,959.79
- Andrews, 2.95 mi. S. of, 70 ft. SW. of rd. fork, 17 ft. W. of rd., at center of ford of McClellan Creek, inside fence, in root on W. side of 15-in. sycamore tree; copper nail and washer, painted "U.S.B.M. 1975.5" 1,975.50
- Andrews, 3.4 mi. S. of, 95 ft. N. of ford across McClellan Creek, 7 ft. W. of rd., in root on SE. side of 350-in. sycamore tree; copper nail and washer, painted "U.S.B.M. 2052.6" 2,052.6 )
- Andrews, 3.52 mi. S. of, Ford over McClellan Creek 2,070.8
- Andrews, 3.64 mi. S. of, Ford over McClellan Creek 2,100.2

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By C.W. MOORE, 1936 ALTITUDE ABOVE  
MEAN SEA LEVEL  
(Feet)

ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK. B7005

RECOPY 12/8/55 Lmk

CLAY, CHEROKEE AND GRAHAM COUNTY

NGVD 29  
Elevations

-21-

Andrews, 3.77 mi. S. of, ford over McClellan Creek	2,127.9
Andrews, 3.82 mi. S. of, 50 ft. S. and 6.2 ft. above rd. forks, 130 ft. S. of ford over McClellan Creek, 110 ft. NE. of ford over McClellan Creek Branch, 8 ft. N. of Forest Service telephone pole, top of boulder; chiseled square, painted "U.S.B.M. 2142.5"	2,142.574
Andrews, 3.84 mi. S. of, ford over McClellan Creek Branch	2,141.7
Andrews, 3.99 mi. S. of, center of pole bridge over Branch of Trail Creek	2,192.8
Andrews, 4.06 mi. S. of, ford over Trail Creek	2,221.4
Andrews, 4.29 mi. S. of, ford over Trail Creek	2,348.6
✓ Andrews, 4.5 mi. S. of, 60 ft. NW. of ford, over Trail Creek at start of trail, 7 ft. NE. of rd., on rock outcrop; standard tablet stamped "G W M 118 1936 2489," painted "U.S.P.B.M. 2488.6"	2,488.667
Reference mark, 54 ft. SW. of tablet, 15 ft. N. of Trail Creek ford, 7 ft. NE. of end of rd., on rock outcrop; chiseled square,	2,493.14
Andrews, 4.95 mi. S. of, 42 ft. NW. of trail forks, 10 ft. W. and 7 ft. above trail, in root on E. side of 14-in. hickory tree; copper nail and washer, painted "U.S.B.M. 2975.6"	2,975.59
Andrews, 5.5 miles S. of, on point of ridge, 120 ft. SE. of sharp bend in trail, 5 ft. SW. of trail, in root on NE. side of 10-in. oak tree; copper nail and washer, painted "U.S.B.M. 3546.5"	3,546.48
Andrews, 6.1 mi. S. of, at top of Valley River Mountain ridge, 60 ft. W. of Forest Service signpost, 55 ft. W. and 1 ft. above trail fork, 14 ft. N. of ridge trail, in root on SW. side of 40-in. oak tree; copper nail and washer, painted "U.S.B.M. 4075.3"	4,075.29
Andrews, 6.55 mi. S. of, on ridge trail, 0.44 mi. W. of McClellan trail fork, at point where side ridge extends southward, 20 ft. S. of trail, in root on NE. side of 250-in. oak tree; copper nail and washer, painted "U.S.B.M. 4290.1"	4,290.08
Andrews, 7.1 mi. S. of, 0.12 mi. E. of Big Stamp Knob Fire tower, 25 ft. SE. of trail forks, 20 ft. SE. of Forest Service signpost, in root on E. side of 17-in. chestnut oak tree; copper nail and washer, painted "U.S.B.M. 4263.4"	4,263.44

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA By C.W. MOORE, 1936 ALTITUDE ABOVE  
MEAN SEA LEV )  
ORDER THIRD ADJ. 1929 GENERAL ADJUSTMENT (Feet)  
BK. B7005  
RECOPY 12/8/55 lmk CLAY, CHEROKEE AND GRAHAM COUNTY

-22-

Andrews, 7.25 mi. S. of, at Big Stamp Knob Fire Tower, 25 ft. N. of Ridge Trail, on concrete base at NW. corner of lower and 4.26 ft. below base of iron work; standard tablet stamped "C. W. M. 119 1936 4437", painted "U.S.P.B.M. 4436.8"	4,436.853
Reference mark, 25 ft. SE. of tablet, top of SE. concrete base of Big Stamp Fire Tower; chiseled square	4,441.12
Andrews, 7.7 mi. S. of, 0.63 mi. S. of Big Stamp Lookout Tower, on trail ridge, 13 ft. W. of trail, in root on NW. side of 14-in. hickory tree; copper nail and washer, painted "U.S.B.M. 4487.9"	4,287.89
Andrews, 8.12 mi. S. of, 1.11 mi. S. of Big Stamp Lookout Tower, on trail ridge, on side of hill, 8 ft. NW. of trail, in root on E. side of 28-in. oak tree; copper nail and washer, painted "U.S.B.M. 4083.8"	4,083.79
Andrews, 8.66 mi. S. of, 1.65 mi. S. of Big Stamp Lookout tower, on trail ridge, 6 ft. SE. of trail, in root on NW. side of 12-in. oak tree; copper nail and washer, painted "U.S.B.M. 3647.8"	3,647.75
Andrews, 9.1 mi. S. of, on rock point on ridge, 8 ft. E. of trail, top of boulder; standard tablet stamped "C. W. M. 120 1936 3250," painted "U.S.P.B.M. 3249.5"	3,249.525
Reference mark, 37 ft. S. of tablet, 10 ft. E. of trail, on rock outcrop; chiseled square	3,244.57
Andrews, 9.24 mi. S. of, 30 ft. E. of trail forks, 4 ft. N. of trail along telephone line, in root on W. side of 12-in. oak tree; copper nail and washer, painted "U.S.B.M. 3086.4"	3,086.40
Andrews, 9.62 mi. S. of, trail fork at foot of hill painted "2381.753"	2,381.7
Andrews, 9.73 mi. S. of, 0.11 mi. SE. of trail forks, at foot of ridge, on NW. bank of Fires Creek, 135 ft. SE. of Bristol's home, 5 ft. S. of S. corner of spring house, 12 ft. SE. of trail passing through yard, in root on NW. side of 32-in. oak tree; copper nail and washer, painted "U.S.B.M. 2340.4"	2,340.41
Andrews, 10.23 mi. S. of, 0.5 mi. W. of Bristol's house, at foot of ridge, 65 ft. N. of wagon rd. at a trail fork to W., in rocky clearing, top of boulder; chiseled square, painted "U.S.B.M. 2303.2"	2,303.14
Andrews, 10.7 mi. S. of, at hairpin turn in wagon rd., 12 ft. SE. of rd., 6 ft. S. of start of foot path to Bristol's house, at rock ledge, top of boulder; chiseled square, painted "U.S.B.M. 2655.8"	2,655
Reference mark, 110 ft. SE. of tablet, 30 ft. SE. of rd., at top of pass, 2.7 ft. above saddle, in root on NW. side of 30-in. oak tree; copper nail and washer	2,997.76

ORDER THIRD

Adj. 1929 GENERAL ADJUSTMENT

BK. B7005

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTY

-23-

- ✓ Andrews, 11.16 mi. S. of, 80 ft. W. of saddle at pass, 8 ft. N. of rd. and 4 ft. above rd., on rock outcrop; standard tablet stamped "G W M 121 1936 2996", painted "U.S.P.B.M. 2996.5" 2,996.448
- Andrews, 11.83 mi. S. of, 0.67 mi. S. of gap, in a saddle in a narrow ridge, 8 ft. W. of rd., in root on E. side of 25-in. yellow pine tree; copper nail and washer, painted "U.S.B.M. 2557.2" 2,557.15
- Andrews, 12.0 mi. S. of, top of hill, ground at center of rd. 2,629.1
- NGVD 29  
Elevations
- BK. B7005, B7018
- Andrews, 12.33 mi. S. of, 1.17 mi. S. of gap, in saddle, 11 ft. SE. of rd., in root on W. side of 20-in. oak tree; copper nail and washer, painted "U.S.B.M. 2414.3" 2,414.28
- ~~Andrews, 12.8 mi. S. of, 0.5 mi. N. of rd. N. to Andrews, at top of hill, 6 ft. E. of rd., in root on W. side of 6-in. oak tree; copper nail and washer, painted "U.S.B.M. 2237.1" 2,237.08~~
- FROM ANDREWS N. ALONG RD. INTO ROBBINSVILLE QUADRANGLE
- ✓ Andrews, 995 ft. E. of milepost 107, 990 ft. E. of Andrews Deptl., 35 ft. N. of N. rail and 6 inches below base of rail, 10 inches above grade, in top of concrete post; U.S.C. & G.S. standard disk stamped "H 54 1933." 1,775.574
- Andrews, 0.44 mi. E. of depot, at rd. N. to Robbinsville, center of R. R. crossing 1,776.0
- Andrews, 0.63 mi. NE. of sta., 350 ft. NE. of entrance to Prison Camp, at concrete highway bridge over Valley River, at E. end of N. concrete guard of bridge; chiseled square, painted "U.S.B.M. 1772.4" 1,772.45
- ✓ Andrews, 1.2 mi. NE. of, 35 ft. NE. of center of wood bridge over Pile Creek, 65 ft. NE. of crossroads, 1.2 ft. above crossroads, in base on E. side of 8-in. sycamore tree; spike, painted white, painted "U.S.B.M. 1824.6" 1,824.69
- Andrews, 1.75 mi. N. of, on grade about 350 ft. SW. of drain, 12 ft. W. of rd., in base on NE. side of 6-in. hickory tree; R. R. spike, painted white, painted "U.S.B.M. 1961.7" 1,961.80
- Bk. B7018
- NOT FOUND 1978
- ✓ Andrews, 2.3 mi. N. of, 30 ft. E. of rd., at curve, at N. edge of trail, top of boulder; standard tablet stamped "G W M 122 1936 2092," painted "U.S.P.B.M. 2092.3" 2,092.338
- NOT FOUND 1978

QUAD. BIG STAMP KNOB	STATE NORTH CAROLINA	BY C.W. MOORE, 1936	ALTITUDE ABOVE MEAN SEA LEVEL (Feet)
ORDER THIRD BK. B7018 RECOPY 12/8/55 lmk	ADJ. 1929 GENERAL ADJUSTMENT	CLAY, CHEROKEE AND CHATHAM COUNTIES	
Reference mark, 205 ft. NW. of table, 22 ft. S. of rd., at curve and 6 ft. below rd., in root on N. side of 9-in. tickery tree; copper nail and washer			2,082.55
Andrews, 2.6 mi. N. of, ground at wood rd. fork W.			2,173.5
Andrews, 3.0 mi. N. of, 95 ft. W. of trail fork, 60 ft. SW. of rd. at curve, 12 ft. N. of trail, in root on R. side of 25-in. red oak tree; copper nail and washer, painted "U.S.B.M. 2319.0"			2,310.68
Andrews, 3.95 mi. N. of, 100 ft. NE. of a end of a grade, 110 ft. NE. of an old rd. crossing, 23 ft. SE. of rd., 6.4 ft. below rd., in root on NW. side of 10-in. oak tree; copper nail and washer, painted "U.S.B.M. 2726.3"			2,726.39
Andrews, 4.3 mi. N. of, 22 ft. S. of rd. at hairpin turn, top of boulder; standard tablet stamped "U.S.B.M. 2865.6", painted "U.S.B.M. 2865.6" <del>DESTROYED 1978</del>			2,865.622
Reference mark, 20 ft. S. of table, 45 ft. S. of hairpin bend, in root on NW. side of 14-in. maple tree; copper nail and washer			2,871.0
Andrews, 4.8 mi. N. of, 50 ft. N. of saddle, 20 ft. W. of rd., on bank, 2.4 ft. above rd., in root on W. side of 15-in. oak tree; copper nail and washer, painted "U.S.B.M. 3079.4"			3,079.42
Andrews, 5.25 mi. N. of, 65 ft. N. of saddle, 20 ft. E. of rd., on bank, 5.7 ft. above rd., in root on W. side of 16-in. oak tree; copper nail and washer, painted "U.S.B.M. 3254.0"			3,254.11
FROM LONG BOTTOMS NE. ALONG TRAIL DOWN LITTLE SNOWBIRD CREEK INTO ROBBINSVILLE QUADRANGLE			
Water at ford of Little Snowbird Creek, at plank foot-bridge, about 200 ft. SE. of house			2,968.5
Marble, 5.3 mi. N. to Long Bottoms, thence 0.73 mi. NE. from, 34 ft. NE. of E. side of ford over Little Snowbird Creek, 7 ft. W. of trail, top of prominent rock outcrop; chiseled square, painted "U.S.B.M. 2919.1"			2,919.16
Long Bottoms, 0.8 mi. NE. of, water elevation at ford, at junction of Little Snowbird Creek and Nelson Cove Branch			2,901.5
Robbinsville, 16.4 mi. SW. of, 5.3 mi. N. of Marble to Long Bottoms, thence 1.23 mi. NE. of along trail on S. side of Little Snowbird Creek (3 channels) 70 ft. E. of center line of power line, 15 ft. N. of trail, in root on N. side of 8-in. ash tree; copper nail and washer, painted "U.S.B.M. 2868.1"			2,868.10



QUAD. BIG STAMP KNOB

STATE NORTH CAROLINA

By G.W. MOORE, 1936

ALTITUDE ABOVE  
MEAN SEA LEVEL  
(Feet)

ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK.B7018

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTY

-25-

Robbinsville, 15.74 mi. SW. of, 630 ft. W. of house, at W. end of small meadow, 90 ft. N. of center line of T.V.A. power line, 6 ft. S. of trail, at W. edge of ford, 1.2 ft. above Little Snowbird Creek, top of boulder; chiseled square, painted "U.S.B.M. 2672.0"	2,671.99
BK.B7019	
FROM BLAIRSVILLE QUADRANGLE N. ALONG RD. TO A POINT ABOUT 4.6 MI. SE. OF HAYESVILLE	NGVD 29 Elevations
Hiwassee, Ga., 4.3 mi. N. of courthouse, 175 ft. SE. of SE. corner of Philadelphia Church, 25 ft. E. of rd., in pasture, in root on W. side of 16-in. oak tree; copper nail and washer, painted "U.S.B.M. 1947.3"	1,947.22
Hiwassee, 4.7 mi. N. of courthouse, 35 ft. NW. of NW. corner of closed store, 9 ft. E. of rd., in base on W. side of 25-in. persimmon tree; R.R. spike, painted white, painted "U.S.B.M. 1941.5"	1,941.45
Hiwassee, 5.16 mi. N. of courthouse, about 1.9 mi. N. of North Carolina-Georgia State line, 65 ft. NW. of rd. fork NW., 22 ft. SW. of rd., at SW. edge of rd. NW., on rock outcrop; standard tablet stamped "G.W.M. 136 1936 1925," painted "U.S.P.B.M. 1925.3"	1,925.199
Reference mark, 90 ft. SE. of tablet, 25 ft. SW. of rd., in root on NE. side of 30-in. oak tree; copper nail and washer	1,927.78
Hiwassee, 5.65 mi. N. of courthouse, 0.4 mi. S. of State Highway 28, 28 ft. W. of rd., 4.6 ft. below rd., in root on NE. side of 12-in. oak tree; copper nail and washer, painted "U.S.B.M. 1890.7"	1,890.65
Hayesville, N. C., 4.25 mi. SE. of courthouse, 6.04 mi. N. of Hiwassee, Ga. courthouse, 110 ft. NE. of steel bridge over Shooting Creek, 21 ft. S. and 10 ft. W. of intersection of center line of State Highway 28 and rd. S., in triangle of rd. fork, about 1.6 ft. above highway, on rock outcrop; chiseled square, painted "U.S.B.M. 1956.2"	1,856.14
Center of steel bridge over Shooting Creek, 12 ft. above water	1,830.5
Hayesville, about 4.65 mi. SE. of Courthouse, at concrete culvert over Licklog Creek, on NW. corner of W. end of S. heading of large concrete culvert; chiseled square, painted "U.S.B.M. 1846.2"	1,847.42

QUAD. BIG STAMP KNOB STATE NORTH CAROLINA BY C.W. MOORE, 1936 ALTITUDE ABOVE  
 MEAN SEA LEVEL )  
 ORDER THIRD ADJ. 1929 GENERAL ADJUSTMENT (Feet)  
 BK. B7019  
 RECOPY 12/8/55 mlk CLAY, CHEROKEE AND WELLSBORO COUNTY  
 -26-

FROM BLAIRSVILLE QUADRANGLE NW. ALONG RD. TO JUNCTION OF MATTHEWSON  
 COVE ROAD AND HIGHWAY 64

Wood Grove Church, 2.31 mi. NW. of, about 100 ft. N. of sheet edge,  
 15 ft. E. of rd., at curve, 5 ft. above rd., in root on W. side of  
 10-in. oak tree; copper nail and washer, painted "U.S.B.M. 200.1" 2,000.07

Reference mark, 62 ft. SW. of tablet, 11 ft. SE. of rd., on rock outcrop;  
 chiseled square 1,926.81

Wood Grove Church, 2.82 mi. NW. of, 65 ft. S. of ford at Mill Creek, 22  
 ft. SE. of rd., 5 ft. W. of fence, on rock outcrop; standard tablet  
 stamped "C W M 139 1936 1922," painted "U.S.P.B.M. 1922.2" 1,922.154

Mill Creek Ford 1,917.990

Wood Grove Church, 3.13 mi. NW. of, 32 ft. W. of rd. forks SW., top of  
 hill on 4 ft. bank, in root on W. side of 6-in. oak tree; copper nail  
 and washer, painted "U.S.B.M. 2020.1" 2,020.04

Road fork elev. 2,016.2

Wood Grove Church, 3.71 mi. NW. of, top of hill, 22 ft. N. of rd., in  
 root on SW. side of 12-in. oak tree, copper nail and washer, painted  
 "U.S.B.M. 2101.1" 2,101.09

Top of hill elevation 2,099.8

Wood Grove Church, 4.16 mi. NW. of, ford over Branch of Coleman Creek 2,081.5

Wood Grove Church, 4.31 mi. NW. of, 50 ft. N. of private rd. fork SW.,  
 20 ft. SW. of ford over Matthewson Cove, Branch of Coleman Creek, 7  
 ft. W. of rd., on rock outcrop; chiseled square, painted "U.S.B.M.  
 2156.1" 2,156.09

Ford elevation 2,154.0

Wood Grove Church, 4.7 mi. NW. of, top of Cherry Mountain ridge, 25 ft.  
 W. of rd. at curve, at point of ridge, 5 ft. above rd., in root on NE.  
 side of 10-in. oak tree; copper nail and washer, painted "U.S.B.M.  
 2317.4" 2,317.41

Reference mark, 30 ft. NE. of tablet, 9 ft. N. of rd., top of boulder;  
 chiseled square 2,243.98

Wood Grove Church, 4.9 mi. NW. of, 0.2 mi. NW. of point of Cherry Mountain  
 ridge, 11 ft. S. of Matthewson Cove rd., 3.5 ft. above rd., on rock  
 outcrop; standard tablet stamped "U.W.M. 146 1936 2245," painted "U.S.P.B.M.  
 2245.3" 2,245.249

QUAD. BIG STAMP KNOB

STATE NORTH CAROLINA

By C.W. MOORE, 1936

ALTITUDE ABOVE  
MEAN SEA LEVEL  
(Feet)

ORDER THIRD

ADJ. 1929 GENERAL ADJUSTMENT

BK.B7019

RECOPY 12/8/55 lmk

CLAY, CHEROKEE AND GRAHAM COUNTY

-27-

Wood Grove Church, 5.35 mi. NW. of, 0.55 mi. SE. of U. S. Highway  
64, 10 ft. N. of Matthewson Cove rd., in root on N. side of 10-in.  
oak tree; copper nail and washer, painted "U.S.B.M. 2081.9"

2,081.93

BK.B7207

FROM BLAIRSVILLE QUADRANGLE NEAR PINELOG CHURCH, ALONG HIGHWAYS NE.  
TO POINT 2 MI. SE. OF BRASSTOWN.

Brasstown, 1.9 mi. SE. along U. S. Highway 64, thence 1.35 mi. S. along  
Pinelog rd., 40 ft. E. of rd. fork SE., 27 ft. SE. of rd., at top  
of hill, 2 ft. above rd., at top of hill, in root on NW. side of 12-in.  
oak tree; copper nail and washer, painted "U.S.B.M. 1873.3"

1,873.36

Elevation of rd. forks

1,770.4

Tablet "G W M 174, 1936," 0.1 mi. S. of, center of plank bridge, 4.1  
ft. above water

1,732.7

Brasstown, 1.9 mi. SE. along U. S. Highway 64, thence 0.75 mi. S. along  
Pinelog rd., 0.1 mi. N. of plank bridge over branch creek, 115 ft.  
NW. of rd., at NW. edge of straightened creek, on J. R. Payne property,  
on large boulder; standard tablet stamped "G W M 174 1936 1712,"  
painted "U.S.P.B.M. 1712.2"

1,712.220

Reference mark, 140 ft. E. of tablet, 7 ft. SE. of rd., in root on SW.  
side of 9-in. oak tree; copper nail and washer

1,720.13

Brasstown, 1.9 mi. SE. thence 0.45 mi. S. from; ford over creek

1,676.3

NGVD 29  
Elevations

GWM 79 RESET

89-07-18

REQ "PRT"			89/07/18-13:45-078-00-00			89/07/18-13:47-078-00-00		
1. TO 1.			1. TO 2.			2. TO 1.		
BS=				1.			1.	
	2.00	***		133.51	***		128.06	***
	23.33	***		134.80	***		129.70	***
	864.67	***		435.07	***		429.61	***
	864.68	***						
FS=				1.			1.	
	2.00	***		133.65	***		127.89	***
	23.33	***		134.70	***		128.80	***
	864.64	***		435.21	***		429.45	***
	864.66	***						
				-0.67			0.67	
			BS=			BS=		
				1.00	***		1.00	***
				12.00	***		11.33	***
	0.05	***		435.06	***		429.61	***
DE=				435.07	***		429.61	***
	0.0003	***						
ELEV=			FS=			FS=		
	478.2310	***		1.00	***		1.00	***
	478.2313	***		11.33	***		12.00	***
1.				435.20	***		429.44	***
89/07/18-13:45-078-00-00				435.21	***		429.45	***
			KM=			KM=		
				0.02	***		0.02	***
			DE=			DE=		
				-0.0014	***		0.0017	***
			ELEV=			ELEV=		
				478.2310	***		478.2296	***
				478.2296	***		478.2313	***
			2.			1.		
			89/07/18-13:47-078-00-00			89/07/-00-00		

SSN 1 - GWM 79

SSN 2 - GWM 79 RESET

USGS QUAD 92

CHEROKEE COUNTY  
NEW BM SET

ON NEW HEADWAL  
ABOUT 8 FEET  
FROM OLD HEADWA

GWM 79 RESET  
ALONG US 64 NEAR  
PEACHTREE



N C GEODETIC SURVEY  
 \*41\*Leveling Running Record

Date of Running (YYMMDD) 89-07-18  
 Starting Point Serial Number 1 Station Name GWM 79  
 Ending Point Serial Number 2 Station Name GWM 79 RESET  
 Starting Time of Running 13:45  
 Ending Time of Running 13:47  
 Air Temperature at Starting Time 78  
 Air Temperature at Ending Time 78  
 Wind Code 00  
 Sun Code 00  
 Number of Setups in Run 1  
 Sum of Backsight Stadia Intercepts 435.1  
 Sum of Foresight Stadia Intercepts 435.1

Length of Run 0.02 (KM) ELEVATION DIFFERENCE (-)0.0014 (MT)  
 Initials of Observer WCB

Starting Point Serial Number 2 Station Name GWM 79 RESET  
 Ending Point Serial Number 1 Station Name GWM 79  
 Starting Time of Running 13:47  
 Ending Time of Running 13:50  
 Air Temperature at Starting Time 78  
 Air Temperature at Ending Time 78  
 Wind Code 00  
 Sun Code 00  
 Number of Setups in Run 1  
 Sum of Backsight Stadia Intercepts 429.4  
 Sum of Foresight Stadia Intercepts 429.4

Length of Run 0.02 (KM) ELEVATION DIFFERENCE 0.0017 (MT)  
 Initials of Observer WCB

Starting Point Serial Number \_\_\_\_\_ Station Name \_\_\_\_\_  
 Ending Point Serial Number \_\_\_\_\_ Station Name \_\_\_\_\_  
 Starting Time of Running \_\_\_\_\_  
 Ending Time of Running \_\_\_\_\_  
 Air Temperature at Starting Time \_\_\_\_\_  
 Air Temperature at Ending Time \_\_\_\_\_  
 Wind Code \_\_\_\_\_  
 Sun Code \_\_\_\_\_  
 Number of Setups in Run \_\_\_\_\_  
 Sum of Backsight Stadia Intercepts \_\_\_\_\_  
 Sum of Foresight Stadia Intercepts \_\_\_\_\_

Length of Run \_\_\_\_\_ (KM) ELEVATION DIFFERENCE \_\_\_\_\_ (MT)  
 Initials of Observer \_\_\_\_\_

NGVD 29  
 Elevations

(File:FRMABSTR)

ROD WILD 3630  
 INSTRUMENT NI-2

NC GEODETIC SURVEY: STATION DESCRIPTION

SSN \_\_\_\_\_ DR CODE D REC CODE \_\_\_\_\_ LAT 35-04-40 LONG 83-58-29  
 APPROX ELEV 478.229 m  
 DESIGNATION GWM 79 RESET COUNTY \_\_\_\_\_  
 TR CODE C PACK TIME 0000 APP \_\_\_\_\_

CODE/SET BY S, NCGS YEAR 1989 CHIEF PAC  
 CODE/RECOVERY 1 DATE 1/1 CHIEF \_\_\_\_\_ CONDITION \_\_\_\_\_  
 TYPE \_\_\_\_\_ MAG CODE \_\_\_\_\_ CODE/SETTING 1  
 STABILITY CODE \_\_\_\_\_ AGENCY INSCRIPTION \_\_\_\_\_  
 STAMPING GWM 79 RESET 1936-1989

RECOVERY NOTE \_\_\_\_\_ PUB HORIZ POS BY \_\_\_\_\_ PUB VERT POS BY NGVD 29  
 Elevations

STATION IS LOCATED:  
 Approximately 3.0 Kms SIN of PEACHTREE  
5.5 Kms ESE of MURPHY

In \_\_\_\_\_  
 At the \_\_\_\_\_

(Proceed) Along US 64 For 1.4 Mi

NW (bearing) from THE NC 141 INTERSECTION (HEAR COMMUNITY IN PEACHTREE)  
NEAR TRI-COUNTY TECHNICAL COLLEGE), OR 0.3 KM  
E. FROM SR 1531, AT W. END OF  
SOUTH HEADWALL OVER PEACHTREE CREEK.

Station Is A Standard:  NCGS  USGS  NGS  NCDOT   
 Horiz Disk  Az Mk Disk  Bench Mark Disk  
 Other DRILLED INTO SET IN DRILLED HOLE IN CONC HEADWALL  
 Set in top of a concrete:  Monument  Cylinder  Post

Mark is \_\_\_\_\_ feet  Lower  Higher Than  Level \_\_\_\_\_  
 And is  Projecting \_\_\_\_\_ inches above  Recessed \_\_\_\_\_ inches below  
 Flush with ground level.

6.6 m S of the centerline of US HIGHWAY

- \_\_\_\_\_ m \_\_\_\_\_ of \_\_\_\_\_  tag
- \_\_\_\_\_ m \_\_\_\_\_ of \_\_\_\_\_  tag
- \_\_\_\_\_ m \_\_\_\_\_ of \_\_\_\_\_  tag
- \_\_\_\_\_ m \_\_\_\_\_ of \_\_\_\_\_  tag
- \_\_\_\_\_ m \_\_\_\_\_ of \_\_\_\_\_  tag

Elevation = 478.229 m ✓